

# AFS ST U (3000 / 6000 PSI)

SAE prirubnica za navarivanje, colna

**HANSA FLEX**

## Karakteristike

|                    |                                      |
|--------------------|--------------------------------------|
| Norma              | SAE J 518 C<br>ISO 6162              |
| Oblik izrade       | ravno                                |
| Izvedba            | SAE prirubnica za navarivanje, colna |
| Pričvršćenje       | vijčani provrt                       |
| Opseg isporuke     | s UNC kompletom vijaka i O prstenom  |
| Materijal          | S355J2G3 (ST52.3)                    |
| Površinska zaštita | crno nauljeno                        |



## Napomena

Navedeni maksimalni radni tlak odnosi se na prirubnicu! Stvarni radni tlak određuje cijev (debljina stjenke) i kvaliteta cijevi!

## Artikli

| Naziv            | Tlačni niz | PB 10.9 (bar) | Veličina | A (mm) | Ø B (mm) | C (mm) | D (mm) | E (mm) | F (mm) | G (mm) | H (mm) | L (mm) | M unc          |
|------------------|------------|---------------|----------|--------|----------|--------|--------|--------|--------|--------|--------|--------|----------------|
| AFS 80 ST U      | 3000 PSI   | 350           | 1/2"     | 21,6   | 13       | 38,1   | 54     | 17,5   | 46     | 36     | 16     | 9,0    | 5/16" x 1.1/4" |
| AFS 80 ST 038 U  | 3000 PSI   | 350           | 1/2"     | 17,5   | 13       | 38,1   | 54     | 17,5   | 46     | 36     | 16     | 9,0    | 5/16" x 1.1/4" |
| AFS 100 ST U     | 3000 PSI   | 350           | 3/4"     | 28,0   | 19       | 47,6   | 65     | 22,2   | 50     | 36     | 18     | 11,0   | 3/8" x 1.1/2"  |
| AFS 102 ST U     | 3000 PSI   | 315           | 1"       | 34,0   | 25       | 52,4   | 70     | 26,2   | 55     | 38     | 18     | 11,0   | 3/8" x 1.1/2"  |
| AFS 104 ST U     | 3000 PSI   | 250           | 1.1/4"   | 42,8   | 32       | 58,7   | 79     | 30,2   | 68     | 41     | 21     | 11,5   | 7/16" x 1.1/2" |
| AFS 106 ST U     | 3000 PSI   | 200           | 1.1/2"   | 48,6   | 38       | 69,9   | 93     | 35,7   | 78     | 44     | 25     | 13,5   | 1/2" x 1.3/4"  |
| AFS 108 ST U     | 3000 PSI   | 200           | 2"       | 61,0   | 51       | 77,8   | 102    | 42,9   | 90     | 45     | 25     | 13,5   | 1/2" x 1.3/4"  |
| AFS 110 ST U     | 3000 PSI   | 160           | 2.1/2"   | 77,0   | 63       | 88,9   | 114    | 50,8   | 105    | 50     | 25     | 13,5   | 1/2" x 1.3/4"  |
| AFS 112 ST U     | 3000 PSI   | 138           | 3"       | 92,0   | 73       | 106,4  | 134    | 61,9   | 124    | 50     | 27     | 17,5   | 5/8" x 2"      |
| AFS 114 ST U     | 3000 PSI   | 35            | 3.1/2"   | 103,0  | 89       | 120,7  | 152    | 69,9   | 136    | 48     | 27     | 17,5   | 5/8" x 2"      |
| AFS 116 ST U     | 3000 PSI   | 35            | 4"       | 115,1  | 99       | 130,2  | 162    | 77,8   | 146    | 48     | 27     | 17,5   | 5/8" x 2"      |
| AFS 401 ST 012 U | 6000 PSI   | 400           | 1/2"     | 21,5   | 13       | 40,5   | 54     | 18,2   | 46     | 36     | 16     | 9,0    | 5/16" x 1.1/4" |
| AFS 401 ST 038 U | 6000 PSI   | 400           | 1/2"     | 17,5   | 13       | 40,5   | 54     | 18,2   | 46     | 36     | 16     | 9,0    | 5/16" x 1.1/4" |
| AFS 402 ST U     | 6000 PSI   | 400           | 3/4"     | 28,0   | 19       | 50,8   | 71     | 23,8   | 55     | 35     | 21     | 11,0   | 3/8" x 1.1/2"  |
| AFS 403 ST U     | 6000 PSI   | 400           | 1"       | 34,0   | 25       | 57,2   | 79     | 27,8   | 68     | 41     | 21     | 13,0   | 7/16" x 1.3/4" |
| AFS 404 ST U     | 6000 PSI   | 375           | 1.1/4"   | 42,8   | 32       | 66,7   | 93     | 31,8   | 78     | 44     | 25     | 15,0   | 1/2" x 1.3/4"  |
| AFS 405 ST U     | 6000 PSI   | 250           | 1.1/2"   | 48,6   | 38       | 79,4   | 112    | 36,5   | 94     | 55     | 30     | 17,0   | 5/8" x 2"      |
| AFS 406 ST U     | 6000 PSI   | 250           | 2"       | 61,0   | 51       | 96,8   | 134    | 44,5   | 114    | 65     | 37     | 21,0   | 3/4" x 2.1/2"  |

PN = nazivni tlak PB = maks. radni tlak

## Varijante proizvoda

|                            |   |
|----------------------------|---|
| AFS ST (3000 PSI)          | SAE prirubnica za navarivanje, colna, samo prirubnica                           |
| AFS ST M (3000 / 6000 PSI) | SAE prirubnica za navarivanje, colna, s kompletom metričkih vijaka i O prstenom |