

T BL

SAE blok prirubnica, T oblik

HANSA FLEX

Karakteristike

Tlačni niz 6000 psi


Norma SAE J 518 C
ISO 6162

Oblik izrade T oblik

Izvedba SAE blok prirubnica

Pričvršćenje Unutarnji navoji za metr. vijke

Materijal S355J2G3 (ST52.3)



Artikli

| Naziv | PB 10.9 (bar) | Veličina | Ø B (mm) | C (mm) | D (mm) | E1 (mm) | E2 (mm) | F (mm) | G (mm) | M metr. |
|--------------|------------------|----------|-------------|-----------|-----------|------------|------------|-----------|-----------|---------|
| T BL 602-602 | 400 | 3/4" | 19 | 50,8 | 72 | 23,8 | 23,8 | 72 | 55 | M 10 |
| T BL 603-603 | 400 | 1" | 23 | 57,2 | 82 | 27,8 | 27,8 | 82 | 64 | M 12 |
| T BL 604-604 | 400 | 1.1/4" | 30 | 66,7 | 100 | 31,8 | 31,8 | 92 | 72 | M 14 |
| T BL 605-605 | 400 | 1.1/2" | 38 | 79,4 | 110 | 36,5 | 36,5 | 98 | 98 | M 16 |
| T BL 606-606 | 400 | 2" | 50 | 96,8 | 133 | 44,5 | 44,5 | 140 | 105 | M 20 |

PN = nazivni tlak PB = maks. radni tlak