

### Karakteristike

<b>Izvedba</b>	Priključak za crpku (3 rupe)
<b>Oblik izrade</b>	Kutevi 90°
<b>Pričvršćenje</b>	s kompletom metričkih vijaka
<b>Opseg isporuke</b>	s kompletom metričkih vijaka i O prstenom
<b>Materijal</b>	aluminij



### Napomena

Navedeni maksimalni radni tlak odnosi se na priрубnicu! Stvarni radni tlak određuje cijev (debljina stjenke) i kvaliteta cijevi!

### Artikli

Naziv	Tlak PB (bar)	LK (mm)	A	B (mm)	S1 (mm)	S2 (mm)	L (mm)	Vijci	OR
<b>WDA 0.5 12</b>	180	26	G 1/2" -14	10,0	18	31	5,3	(3 x) M 5 x 35	14,00 x 1,78
<b>WDA 0.5 38</b>	180	26	G 3/8" - 19	10,0	18	31	5,3	(3 x) M 5 x 35	14,00 x 1,78
<b>WDA 1 12</b>	180	30	G 1/2" -14	12,5	18	30	6,5	(3 x) M 6 x 35	15,88 x 2,62
<b>WDA 1 38</b>	180	30	G 3/8" - 19	12,5	18	30	6,5	(3 x) M 6 x 35	15,88 x 2,62
<b>WDA 2 12</b>	180	40	G 1/2" -14	18,5	20	40	8,5	(3 x) M 8 x 45	22,22 x 2,62
<b>WDA 2 34</b>	180	40	G 3/4" -14	18,5	20	40	8,5	(3 x) M 8 x 45	22,22 x 2,62
<b>WDA 3 34</b>	180	51	G 3/4" -14	25,0	26	46	10,5	(3 x) M 10 x 60	29,74 x 3,53
<b>WDA 3 100</b>	180	56	G 1" -11	25,0	26	46	10,5	(3 x) M 10 x 60	29,74 x 3,53

PN = nazivni tlak PB = maks. radni tlak