

FHR 91

Čep s navojem, šesterokutna glava

HANSA FLEX

Karakteristike

| | |
|--------------------|--------------------------------------|
| Priključak 1 | BSP vanjski navoj, cilindrični |
| Oblik brtve 1 | Profil A |
| Izvedba | Čepovi s navojem, šesterokutna glava |
| Oblik izrade | ravno |
| Norma | DIN 910 |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Artikli

| Naziv | G1 | i (mm) | D (mm) | L1 (mm) | L2 (mm) | SW (mm) |
|--------------|---------------|-----------|-----------|------------|------------|------------|
| FHR 91-1/8 | G 1/8" - 28 | 8 | 14 | 17 | 6 | 10 |
| FHR 91-1/4 | G 1/4" - 19 | 12 | 18 | 21 | 6 | 13 |
| FHR 91-3/8 | G 3/8" - 19 | 12 | 22 | 21 | 6 | 17 |
| FHR 91-1/2 | G 1/2" - 14 | 14 | 26 | 26 | 8 | 19 |
| FHR 91-5/8 | G 5/8" - 14 | 14 | 28 | 26 | 8 | 19 |
| FHR 91-3/4 | G 3/4" - 14 | 16 | 32 | 30 | 10 | 24 |
| FHR 91-1 | G 1" - 11 | 16 | 39 | 32 | 11 | 27 |
| FHR 91-1 1/4 | G 1,1/4" - 11 | 16 | 49 | 33 | 12 | 30 |
| FHR 91-1 1/2 | G 1,1/2" - 11 | 16 | 55 | 33 | 12 | 30 |