

# WN VA

Uvrtni vijčani spoj, kut 90°

**HANSA FLEX**

## Karakteristike

|                |   |
|----------------|---|
| Priključak 1   | NPT vanjski navoji                                |
| Oblik brtve 1  | brtvljenje navoja                                 |
| Priključak 2   | metrički vanjski navoji, cilindrični              |
| Oblik brtve 2  | 24° unutarnji konus                               |
| Izvedba        | Uvrtni vijčani spoj                               |
| Oblik izrade   | Kutevi 90°  |
| Norma          | DIN 2353<br>ISO 8434-1                            |
| Opseg isporuke | Nastavak s pretornom maticom i narezanim prstenom |
| Materijal      | Oplemenjeni čelik                                 |



## Napomena

Upute za montažu, ugradnju, tlačno opterećenje i dopuštene radne temperature pronaći ćete u tehničkim informacijama za vijčane spojeve cijevi.

## Artikli

| Naziv              | Seriya | Radni tlak bari | Vanjski Ø cijevi (mm) | G                 | i (mm) | L3 (mm) | L4 (mm) | L5 (mm) | SW (mm) | S3 |
|--------------------|--------|-----------------|-----------------------|-------------------|--------|---------|---------|---------|---------|----|
| WN 04 LL VA        | LL     | PN 100          | 4                     | 1/8" -27 NPT      | 7,0    | 21      | 11,0    | 17      | 9       | 10 |
| WN 06 LL VA        | LL     | PN 100          | 6                     | 1/8" -27 NPT      | 10,0   | 21      | 9,5     | 17      | 9       | 12 |
| WN 08 LL VA        | LL     | PN 100          | 8                     | 1/8" -27 NPT      | 10,0   | 21      | 9,5     | 17      | 12      | 14 |
| WN NW 04 HL VA     | L      | PN 315          | 6                     | 1/8" -27 NPT      | 10,0   | 27      | 12,0    | 20      | 12      | 14 |
| WN NW 04 HL 1/4 VA | L      | PN 315          | 6                     | 1/4" - 18 NPT     | 12,0   | 29      | 14,0    | 26      | 12      | 14 |
| WN NW 04 HL 3/8 VA | L      | PN 315          | 6                     | 3/8" - 18 NPT     | 15,3   | 33      | 18,0    | 28      | 14      | 14 |
| WN NW 04 HL 1/2 VA | L      | PN 315          | 6                     | 1/2" - 14 NPT     | 17,0   | 38      | 23,0    | 34      | 19      | 14 |
| WN NW 06 HL 1/8 VA | L      | PN 315          | 8                     | 1/8" -27 NPT      | 110,0  | 29      | 14,0    | 26      | 12      | 17 |
| WN NW 06 HL VA     | L      | PN 315          | 8                     | 1/4" - 18 NPT     | 12,0   | 29      | 14,0    | 26      | 12      | 17 |
| WN NW 06 HL 3/8 VA | L      | PN 315          | 8                     | 3/8" - 18 NPT     | 15,2   | 23      | 11,5    | 20      | 12      | 17 |
| WN NW 06 HL 1/2 VA | L      | PN 315          | 8                     | 1/2" - 14 NPT     | 17,5   | 30      | 15,0    | 26      | 12      | 17 |
| WN NW 08 HL 1/8 VA | L      | PN 315          | 10                    | 1/8" -27 NPT      | 10,0   | 30      | 15,0    | 27      | 14      | 19 |
| WN NW 08 HL VA     | L      | PN 315          | 10                    | 1/4" - 18 NPT     | 14,0   | 30      | 15,0    | 27      | 14      | 19 |
| WN NW 08 HL 3/8 VA | L      | PN 315          | 10                    | 3/8" - 18 NPT     | 15,2   | 30      | 15,0    | 27      | 14      | 19 |
| WN NW 08 HL 1/2 VA | L      | PN 315          | 10                    | 1/2" - 14 NPT     | 20,0   | 37      | 21,0    | 33      | 17      | 19 |
| WN NW 10 HL 1/4 VA | L      | PN 315          | 12                    | 1/4" - 18 NPT     | 14,0   | 32      | 17,0    | 28      | 17      | 22 |
| WN NW 10 HL VA     | L      | PN 315          | 12                    | 3/8" - 18 NPT     | 12,5   | 32      | 17,0    | 28      | 17      | 22 |
| WN NW 10 HL 1/2 VA | L      | PN 315          | 12                    | 1/2" - 14 NPT     | 19,0   | 38      | 23,0    | 34      | 19      | 22 |
| WN NW 13 HL 3/8 VA | L      | PN 315          | 15                    | 3/8" - 18 NPT     | 13,0   | 36      | 21,0    | 34      | 19      | 27 |
| WN NW 13 HL VA     | L      | PN 315          | 15                    | 1/2" - 14 NPT     | 18,5   | 36      | 21,0    | 34      | 19      | 27 |
| WN NW 16 HL 3/8 VA | L      | PN 315          | 18                    | 3/8" - 18 NPT     | 15,3   | 40      | 23,5    | 36      | 24      | 32 |
| WN NW 16 HL VA     | L      | PN 315          | 18                    | 1/2" - 14 NPT     | 20,0   | 40      | 23,5    | 36      | 24      | 32 |
| WN NW 16 HL 3/4 VA | L      | PN 315          | 18                    | 3/4" - 14 NPT     | 18,5   | 40      | 23,5    | 40      | 24      | 32 |
| WN NW 20 HL 1/2 VA | L      | PN 160          | 22                    | 1/2" - 14 NPT     | 20,0   | 44      | 27,5    | 42      | 27      | 36 |
| WN NW 20 HL VA     | L      | PN 160          | 22                    | 3/4" - 14 NPT     | 18,5   | 44      | 27,5    | 42      | 27      | 36 |
| WN NW 25 HL 3/4 VA | L      | PN 160          | 28                    | 3/4" - 14 NPT     | 20,0   | 47      | 30,5    | 48      | 36      | 41 |
| WN NW 25 HL VA     | L      | PN 160          | 28                    | 1" -11,5 NPT      | 24,0   | 47      | 30,5    | 48      | 36      | 41 |
| WN NW 32 HL VA     | L      | PN 160          | 35                    | 1,1/4" - 11,5 NPT | 25,5   | 56      | 34,5    | 54      | 41      | 50 |
| WN NW 40 HL VA     | L      | PN 160          | 42                    | 1,1/2" - 11,5 NPT | 26,0   | 63      | 40,0    | 61      | 50      | 60 |
| WN NW 03 HS VA     | S      | PN 630          | 6                     | 1/4" - 18 NPT     | 12,0   | 31      | 16,0    | 26      | 12      | 17 |
| WN NW 03 HS 3/8 VA | S      | PN 630          | 6                     | 3/8" - 18 NPT     | 15,3   | 32      | 17,5    | 27      | 14      | 17 |
| WN NW 03 HS 1/2 VA | S      | PN 630          | 6                     | 1/2" - 14 NPT     | 20,0   | 36      | 21,0    | 34      | 17      | 17 |
| WN NW 04 HS VA     | S      | PN 630          | 8                     | 1/4" - 18 NPT     | 15,0   | 32      | 17,0    | 27      | 14      | 19 |
| WN NW 04 HS 3/8 VA | S      | PN 630          | 8                     | 3/8" - 18 NPT     | 15,3   | 33      | 18,0    | 28      | 14      | 19 |
| WN NW 04 HS 1/2 VA | S      | PN 630          | 8                     | 1/2" - 14 NPT     | 20,0   | 38      | 23,0    | 34      | 17      | 19 |
| WN NW 06 HS 1/4 VA | S      | PN 630          | 10                    | 1/4" - 18 NPT     | 15,0   | 34      | 17,5    | 28      | 17      | 22 |
| WN NW 06 HS VA     | S      | PN 630          | 10                    | 3/8" - 18 NPT     | 12,0   | 34      | 17,5    | 28      | 17      | 22 |
| WN NW 06 HS 1/2 VA | S      | PN 630          | 10                    | 1/2" - 14 NPT     | 20,0   | 39      | 22,5    | 32      | 17      | 22 |
| WN NW 08 HS 1/4 VA | S      | PN 630          | 12                    | 1/4" - 18 NPT     | 15,0   | 38      | 21,5    | 29      | 17      | 24 |
| WN NW 08 HS VA     | S      | PN 630          | 12                    | 3/8" - 18 NPT     | 12,5   | 38      | 21,5    | 28      | 17      | 24 |
| WN NW 08 HS 1/2 VA | S      | PN 630          | 12                    | 1/2" - 14 NPT     | 20,0   | 39      | 21,5    | 34      | 17      | 24 |
| WN NW 10 HS 3/8 VA | S      | PN 630          | 14                    | 3/8" - 18 NPT     | 15,3   | 40      | 22,0    | 30      | 19      | 27 |
| WN NW 10 HS VA     | S      | PN 630          | 14                    | 1/2" - 14 NPT     | 18,0   | 40      | 22,0    | 34      | 19      | 27 |



Usprkos pažljivoj provjeri ne mogu se isključiti pogreške i zbog toga ne preuzimamo odgovornost za sadržane podatke.

30. 10. 2025

HANSA-FLEX AG

www.hansa-flex.com

1

# WN VA

Uvrtni vijčani spoj, kut 90°

**HANSA FLEX**

## Artikli

| Naziv              | Seriya | Radni tlak bari | Vanjski Ø cijevi (mm) | G                 | i (mm) | L3 (mm) | L4 (mm) | L5 (mm) | SW (mm) | S3 |
|--------------------|--------|-----------------|-----------------------|-------------------|--------|---------|---------|---------|---------|----|
| WN NW 13 HS 3/8 VA | S      | PN 400          | 16                    | 3/8" - 18 NPT     | 15,3   | 43      | 24,5    | 32      | 24      | 30 |
| WN NW 13 HS VA     | S      | PN 400          | 16                    | 1/2" - 14 NPT     | 19,0   | 43      | 24,5    | 36      | 24      | 30 |
| WN NW 13 HS 3/4 VA | S      | PN 400          | 16                    | 3/4" - 14 NPT     | 20,0   | 43      | 25,0    | 40      | 24      | 30 |
| WN NW 16 HS 1/2 VA | S      | PN 400          | 20                    | 1/2" - 14 NPT     | 20,0   | 48      | 26,5    | 42      | 27      | 36 |
| WN NW 16 HS VA     | S      | PN 400          | 20                    | 3/4" - 14 NPT     | 20,0   | 48      | 26,6    | 42      | 27      | 36 |
| WN NW 20 HS VA     | S      | PN 400          | 25                    | 1" - 11,5 NPT     | 24,0   | 54      | 30,0    | 48      | 36      | 46 |
| WN NW 25 HS VA     | S      | PN 400          | 30                    | 1,1/4" - 11,5 NPT | 25,5   | 62      | 35,5    | 54      | 41      | 50 |
| WN NW 32 HS VA     | S      | PN 315          | 38                    | 1,1/2" - 11,5 NPT | 26,0   | 72      | 41,0    | 61      | 50      | 60 |

PN = nazivni tlak PB = maks. radni tlak – Serija: LL = veoma lagan L = lagan S = težak – Ø = vanjski promjer cijevi

## Varijante proizvoda

|        |   |
|--------|---|
| WN     | Uvrtni vijčani spoj, kut 90°, Čelik             |
| WN MG  | Uvrtni vijčani spoj, kut 90°, Mjed              |
| XWN VA | Uvrtni vijčani spoj, kut 90°, Oplemenjeni čelik |