

Karakteristike

| | |
|--------------------|-------------------|
| Priključak 1 | BSP navoji matice |
| Oblik brtve 1 | 60° vanjski konus |
| Priključak 2 | BSP navoji matice |
| Oblik brtve 2 | 60° vanjski konus |
| Izvedba | Spojnice |
| Oblik izrade | ravno |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Artikli

| Naziv | G1 | G2 | S1 | S2 |
|---------------|---------------|---------------|----|----|
| G AB 02 | G 1/8" - 28 | G 1/8" - 28 | 14 | 14 |
| G AB 04 AB 02 | G 1/4" - 19 | G 1/8" - 28 | 19 | 14 |
| G AB 04 | G 1/4" - 19 | G 1/4" - 19 | 19 | 19 |
| G AB 06 AB 04 | G 3/8" - 19 | G 1/4" - 19 | 22 | 19 |
| G AB 06 | G 3/8" - 19 | G 3/8" - 19 | 22 | 22 |
| G AB 08 AB 04 | G 1/2" - 14 | G 1/4" - 19 | 27 | 19 |
| G AB 08 AB 06 | G 1/2" - 14 | G 3/8" - 19 | 27 | 22 |
| G AB 08 | G 1/2" - 14 | G 1/2" - 14 | 27 | 27 |
| G AB 10 AB 06 | G 5/8" - 14 | G 3/8" - 19 | 30 | 22 |
| G AB 10 AB 08 | G 5/8" - 14 | G 1/2" - 14 | 30 | 27 |
| G AB 10 | G 5/8" - 14 | G 5/8" - 14 | 30 | 30 |
| G AB 12 AB 06 | G 3/4" - 14 | G 3/8" - 19 | 32 | 22 |
| G AB 12 AB 08 | G 3/4" - 14 | G 1/2" - 14 | 32 | 27 |
| G AB 12 AB 10 | G 3/4" - 14 | G 5/8" - 14 | 32 | 30 |
| G AB 12 | G 3/4" - 14 | G 3/4" - 14 | 32 | 32 |
| G AB 16 AB 06 | G 1" - 11 | G 3/8" - 19 | 41 | 22 |
| G AB 16 AB 08 | G 1" - 11 | G 1/2" - 14 | 41 | 27 |
| G AB 16 AB 12 | G 1" - 11 | G 3/4" - 14 | 41 | 32 |
| G AB 16 | G 1" - 11 | G 1" - 11 | 41 | 41 |
| G AB 20 AB 16 | G 1,1/4" - 11 | G 1" - 11 | 50 | 41 |
| G AB 20 | G 1,1/4" - 11 | G 1,1/4" - 11 | 50 | 50 |
| G AB 24 | G 1,1/2" - 11 | G 1,1/2" - 11 | 60 | 60 |
| G AB 32 | G 2" - 11 | G 2" - 11 | 70 | 70 |

SW, S1, S2 = širina klučca

Varijante proizvoda

G AB VA Spojnice, Oplemenjeni čelik