

Karakteristike

Priključak 1	BSP navoji matice
Oblik brtve 1	60° vanjski konus
Priključak 2	BSP navoji matice
Oblik brtve 2	60° vanjski konus
Izvedba	Spojnice
Oblik izrade	ravno
Materijal	Čelik
Površinska zaštita	galvanski premaz



Artikli

Naziv	G1	G2	S1	S2
G AB 02	G 1/8" - 28	G 1/8" - 28	14	14
G AB 04 AB 02	G 1/4" - 19	G 1/8" - 28	19	14
G AB 04	G 1/4" - 19	G 1/4" - 19	19	19
G AB 06 AB 04	G 3/8" - 19	G 1/4" - 19	22	19
G AB 06	G 3/8" - 19	G 3/8" - 19	22	22
G AB 08 AB 04	G 1/2" - 14	G 1/4" - 19	27	19
G AB 08 AB 06	G 1/2" - 14	G 3/8" - 19	27	22
G AB 08	G 1/2" - 14	G 1/2" - 14	27	27
G AB 10 AB 06	G 5/8" - 14	G 3/8" - 19	30	22
G AB 10 AB 08	G 5/8" - 14	G 1/2" - 14	30	27
G AB 10	G 5/8" - 14	G 5/8" - 14	30	30
G AB 12 AB 06	G 3/4" - 14	G 3/8" - 19	32	22
G AB 12 AB 08	G 3/4" - 14	G 1/2" - 14	32	27
G AB 12 AB 10	G 3/4" - 14	G 5/8" - 14	32	30
G AB 12	G 3/4" - 14	G 3/4" - 14	32	32
G AB 16 AB 06	G 1" - 11	G 3/8" - 19	41	22
G AB 16 AB 08	G 1" - 11	G 1/2" - 14	41	27
G AB 16 AB 12	G 1" - 11	G 3/4" - 14	41	32
G AB 16	G 1" - 11	G 1" - 11	41	41
G AB 20 AB 16	G 1,1/4" - 11	G 1" - 11	50	41
G AB 20	G 1,1/4" - 11	G 1,1/4" - 11	50	50
G AB 24	G 1,1/2" - 11	G 1,1/2" - 11	60	60
G AB 32	G 2" - 11	G 2" - 11	70	70

SW, S1, S2 = širina klučca

Varijante proizvoda

G AB VA Spojnice, Oplemenjeni čelik