

Karakteristike

| | |
|--------------------|-----------------------|
| Priključak 1 | NPT unutarnji navoj |
| Oblik brtve 1 | brtvljenje navoja |
| Priključak 2 | UN/UNF vanjski navoji |
| Oblik brtve 2 | 74° vanjski konus |
| Izvedba | Spojni nastavci |
| Oblik izrade | ravno |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Artikli

| Naziv | G1 | G2 | SW (mm) |
|---------------|-------------------|----------------|------------|
| G IN 02 HJ 04 | 1/8" -27 NPT | 7/16" -20 UNF | 14 |
| G IN 02 HJ 05 | 1/8" -27 NPT | 1/2" -20 UNF | 14 |
| G IN 04 HJ | 1/4" - 18 NPT | 7/16" -20 UNF | 19 |
| G IN 04 HJ 05 | 1/4" - 18 NPT | 1/2" -20 UNF | 19 |
| G IN 04 HJ 06 | 1/4" - 18 NPT | 9/16" - 18 UNF | 19 |
| G IN 04 HJ 08 | 1/4" - 18 NPT | 3/4" - 16 UNF | 21 |
| G IN 06 HJ | 3/8" - 18 NPT | 9/16" - 18 UNF | 22 |
| G IN 06 HJ 08 | 3/8" - 18 NPT | 3/4" - 16 UNF | 22 |
| G IN 06 HJ 10 | 3/8" - 18 NPT | 7/8" - 14 UNF | 29 |
| G IN 08 HJ | 1/2" - 14 NPT | 3/4" - 16 UNF | 29 |
| G IN 08 HJ 10 | 1/2" - 14 NPT | 7/8" - 14 UNF | 29 |
| G IN 08 HJ 12 | 1/2" - 14 NPT | 1.1/16" -12 UN | 29 |
| G IN 12 HJ | 3/4" - 14 NPT | 1.1/16" -12 UN | 35 |
| G IN 12 HJ 14 | 3/4" - 14 NPT | 1.3/16" -12 UN | 35 |
| G IN 16 HJ | 1" -11,5 NPT | 1.5/16" -12 UN | 41 |
| G IN 20 HJ | 1,1/4" - 11,5 NPT | 1,5/8" -12 UN | 50 |
| G IN 24 HJ | 1,1/2" - 11,5 NPT | 1,7/8" -12 UN | 60 |
| G IN 32 HJ | 2" -11,5 NPT | 2,1/2" -12 UN | 73 |

SW = širina ključa

Varijante proizvoda

G IN HJ VA Spojni nastavci, Oplemenjeni čelik