

G IN HJ VA

Spojni nastavci

HANSA FLEX

Karakteristike

Priključak 1 NPT unutarnji navoj

Oblik brtve 1 brtvljenje navoja


Priključak 2 UN/UNF vanjski navoji

Oblik brtve 2 74° vanjski konus

Izvedba Spojni nastavci

Oblik izrade ravno

Materijal Oplemenjeni čelik



Artikli

Naziv	G1	G2	SW (mm)
G IN 02 HJ 04 VA	1/8" -27 NPT	7/16" -20 UNF	14
G IN 04 HJ VA	1/4" - 18 NPT	7/16" -20 UNF	19
G IN 04 HJ 05 VA	1/4" - 18 NPT	1/2" -20 UNF	19
G IN 04 HJ 06 VA	1/4" - 18 NPT	9/16" - 18 UNF	19
G IN 06 HJ VA	3/8" - 18 NPT	9/16" - 18 UNF	22
G IN 06 HJ 08 VA	3/8" - 18 NPT	3/4" - 16 UNF	22
G IN 08 HJ VA	1/2" - 14 NPT	3/4" - 16 UNF	29
G IN 08 HJ 10 VA	1/2" - 14 NPT	7/8" - 14 UNF	29
G IN 12 HJ VA	3/4" - 14 NPT	1.1/16" -12 UN	35

SW = širina ključa

Varijante proizvoda

G IN HJ Spojni nastavci, Čelik