

Karakteristike

| | |
|---------------------|----------------------------------|
| Priključak 1 | BSP unutarnji navoj, cilindrični |
| Priključak 2 | BSP unutarnji navoj, cilindrični |
| Izvedba | Spojni nastavci |
| Oblik izrade | ravno |
| Materijal | Oplemenjeni čelik |



Artikli

| Naziv | G1 | G2 | SW (mm) |
|----------------------|---------------|---------------|------------|
| G 02 IR VA | G 1/8" - 28 | G 1/8" - 28 | 14 |
| G 04 IR 02 VA | G 1/4" - 19 | G 1/8" - 28 | 17 |
| G 04 IR VA | G 1/4" - 19 | G 1/4" - 19 | 17 |
| G 06 IR 04 VA | G 3/8" - 19 | G 1/4" - 19 | 22 |
| G 06 IR VA | G 3/8" - 19 | G 3/8" - 19 | 22 |
| G 08 IR 04 VA | G 1/2" -14 | G 1/4" - 19 | 27 |
| G 08 IR 06 VA | G 1/2" -14 | G 3/8" - 19 | 27 |
| G 08 IR VA | G 1/2" -14 | G 1/2" -14 | 27 |
| G 12 IR 06 VA | G 3/4" -14 | G 3/8" - 19 | 32 |
| G 12 IR VA | G 3/4" -14 | G 3/4" -14 | 32 |
| G 16 IR 08 VA | G 1" -11 | G 1/2" -14 | 41 |
| G 16 IR 12 VA | G 1" -11 | G 3/4" -14 | 41 |
| G 16 IR VA | G 1" -11 | G 1" -11 | 41 |
| G 20 IR 16 VA | G 1,1/4" - 11 | G 1" -11 | 50 |
| G 20 IR VA | G 1,1/4" - 11 | G 1,1/4" - 11 | 50 |
| G 24 IR 20 VA | G 1,1/2" - 11 | G 1,1/4" - 11 | 55 |
| G 24 IR VA | G 1,1/2" - 11 | G 1,1/2" - 11 | 55 |
| G 32 IR 24 VA | G 2" -11 | G 1,1/2" - 11 | 70 |
| G 32 IR VA | G 2" -11 | G 2" -11 | 70 |

SW = širina ključa

Varijante proizvoda

G IR Spojni nastavci, Čelik