

GE HMO HB

Uvrtni nastavci

Karakteristike

| | |
|---------------------------|--|
| Priključak 1 | metrički vanjski navoji, cilindrični |
| Oblik brtve 1 | O prstenasta brtva na uvrtnom nastavku |
| Priključak 2 | BSP vanjski navoj, cilindrični |
| Oblik brtve 2 | 60° unutarnji konus |
| Izvedba | Uvrtni nastavci |
| Oblik izrade | ravno |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Artikli

| Naziv | G1 | G2 | SW (mm) | OR |
|-----------------|------------|---------------|------------|--------------|
| GE HMO 10 HB 02 | M 10 x 1 | G 1/8" - 28 | 15 | 8,00 x 1,50 |
| GE HMO 12 HB 02 | M 12 x 1,5 | G 1/8" - 28 | 18 | 9,30 x 2,30 |
| GE HMO 12 HB 04 | M 12 x 1,5 | G 1/4" - 19 | 18 | 9,30 x 2,30 |
| GE HMO 14 HB 04 | M 14 x 1,5 | G 1/4" - 19 | 20 | 11,30 x 2,30 |
| GE HMO 14 HB 06 | M 14 x 1,5 | G 3/8" - 19 | 20 | 11,30 x 2,30 |
| GE HMO 16 HB 04 | M 16 x 1,5 | G 1/4" - 19 | 22 | 13,30 x 2,30 |
| GE HMO 16 HB 06 | M 16 x 1,5 | G 3/8" - 19 | 22 | 13,30 x 2,30 |
| GE HMO 18 HB 06 | M 18 x 1,5 | G 3/8" - 19 | 24 | 15,30 x 2,30 |
| GE HMO 18 HB 08 | M 18 x 1,5 | G 1/2" - 14 | 24 | 15,30 x 2,30 |
| GE HMO 20 HB 08 | M 20 x 1,5 | G 1/2" - 14 | 28 | 17,30 x 2,30 |
| GE HMO 22 HB 08 | M 22 x 1,5 | G 1/2" - 14 | 28 | 19,30 x 2,30 |
| GE HMO 22 HB 10 | M 22 x 1,5 | G 5/8" - 14 | 28 | 19,30 x 2,30 |
| GE HMO 22 HB 12 | M 22 x 1,5 | G 3/4" - 14 | 28 | 19,30 x 2,30 |
| GE HMO 27 HB 12 | M 27 x 2 | G 3/4" - 14 | 33 | 23,47 x 2,95 |
| GE HMO 27 HB 16 | M 27 x 2 | G 1" - 11 | 33 | 23,47 x 2,95 |
| GE HMO 33 HB 16 | M 33 x 2 | G 1" - 11 | 42 | 29,74 x 2,95 |
| GE HMO 42 HB 20 | M 42 x 2 | G 1,1/4" - 11 | 50 | 38,00 x 3,00 |
| GE HMO 48 HB 24 | M 48 x 2 | G 1,1/2" - 11 | 56 | 44,00 x 3,00 |

SW = širina ključa