

Karakteristike

Priključak 1	BSP vanjski navoj, konusni
Oblik brtve 1	brtvljenje navoja
Priključak 2	BSP navoji matice
Oblik brtve 2	60° unutarnji konus
Izvedba	Uvrtni nastavci
Oblik izrade	ravno
Materijal	Čelik
Površinska zaštita	galvanski premaz



Artikli

Naziv	G1	G2	SW (mm)	S1
GE HRK 02 AB	R 1/8" K	G 1/8" - 28	14	14
GE HRK 04 AB	R 1/4" K	G 1/4" - 19	19	19
GE HRK 06 AB	R 3/8" K	G 3/8" - 19	22	22
GE HRK 06 AB 08	R 3/8" K	G 1/2" - 14	22	27
GE HRK 08 AB 06	R 1/2" K	G 3/8" - 19	27	22
GE HRK 08 AB	R 1/2" K	G 1/2" - 14	27	27
GE HRK 10 AB	R 5/8" K	G 5/8" - 14	30	30
GE HRK 12 AB 08	R 3/4" K	G 1/2" - 14	37	27
GE HRK 12 AB	R 3/4" K	G 3/4" - 14	37	37
GE HRK 16 AB 12	R 1" K	G 3/4" - 14	41	37
GE HRK 16 AB	R 1" K	G 1" - 11	41	41
GE HRK 20 AB	R 1,1/4" K	G 1,1/4" - 11	50	50
GE HRK 24 AB	R 1,1/2" K	G 1,1/2" - 11	55	60
GE HRK 32 AB	R 2" K	G 2" - 11	64	67

SW, S1, S2 = širina kluča

Varijante proizvoda

GE HRK AB VA	Uvrtni nastavci, Oplemenjeni čelik
---------------------	------------------------------------