


### Karakteristike

Priključak 1	BSP vanjski navoj, konusni
Oblik brtve 1	brtvljenje navoja
Priključak 2	UN/UNF navoji matice
Oblik brtve 2	74° unutarnji konus
Izvedba	Uvrtni nastavci
Oblik izrade	ravno
Materijal	Čelik
Površinska zaštita	galvanski premaz



### Artikli

Naziv	G1	G2	SW (mm)	S1
GE HRK 02 AJ 04	R 1/8" K	7/16" -20 UNF	13	16
GE HRK 02 AJ 05	R 1/8" K	1/2" -20 UNF	13	17
GE HRK 04 AJ	R 1/4" K	7/16" -20 UNF	14	16
GE HRK 04 AJ 05	R 1/4" K	1/2" -20 UNF	14	17
GE HRK 04 AJ 06	R 1/4" K	9/16" - 18 UNF	14	19
GE HRK 04 AJ 08	R 1/4" K	3/4" - 16 UNF	19	22
GE HRK 06 AJ 05	R 3/8" K	1/2" -20 UNF	19	17
GE HRK 06 AJ	R 3/8" K	9/16" - 18 UNF	19	19
GE HRK 06 AJ 08	R 3/8" K	3/4" - 16 UNF	19	22
GE HRK 06 AJ 10	R 3/8" K	7/8" - 14 UNF	22	27
GE HRK 08 AJ	R 1/2" K	3/4" - 16 UNF	27	32
GE HRK 08 AJ 10	R 1/2" K	7/8" - 14 UNF	22	27
GE HRK 08 AJ 12	R 1/2" K	1.1/16" -12 UN	27	32
GE HRK 12 AJ 10	R 3/4" K	7/8" - 14 UNF	27	27
GE HRK 12 AJ	R 3/4" K	1.1/16" -12 UN	27	32
GE HRK 12 AJ 14	R 3/4" K	1,3/16" -12 UN	27	32
GE HRK 12 AJ 16	R 3/4" K	1,5/16" -12 UN	32	38
GE HRK 16 AJ	R 1" K	1,5/16" -12 UN	36	38
GE HRK 16 AJ 12	R 1" K	1.1/16" -12 UN	36	38
GE HRK 20 AJ	R 1,1/4" K	1,5/8" -12 UN	46	50
GE HRK 24 AJ	R 1,1/2" K	1,7/8" -12 UN	54	55

SW, S1, S2 = širina ključa