

Karakteristike

| | |
|--------------------|----------------------------|
| Priključak 1 | BSP vanjski navoj, konusni |
| Oblik brtve 1 | brtvljenje navoja |
| Priključak 2 | UN/UNF navoji matice |
| Oblik brtve 2 | 74° unutarnji konus |
| Izvedba | Uvrtni nastavci |
| Oblik izrade | ravno |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Artikli

| Naziv | G1 | G2 | SW (mm) | S1 |
|-----------------|------------|----------------|------------|----|
| GE HRK 02 AJ 04 | R 1/8" K | 7/16" -20 UNF | 13 | 16 |
| GE HRK 02 AJ 05 | R 1/8" K | 1/2" -20 UNF | 13 | 17 |
| GE HRK 04 AJ | R 1/4" K | 7/16" -20 UNF | 14 | 16 |
| GE HRK 04 AJ 05 | R 1/4" K | 1/2" -20 UNF | 14 | 17 |
| GE HRK 04 AJ 06 | R 1/4" K | 9/16" - 18 UNF | 14 | 19 |
| GE HRK 04 AJ 08 | R 1/4" K | 3/4" - 16 UNF | 19 | 22 |
| GE HRK 06 AJ 05 | R 3/8" K | 1/2" -20 UNF | 19 | 17 |
| GE HRK 06 AJ | R 3/8" K | 9/16" - 18 UNF | 19 | 19 |
| GE HRK 06 AJ 08 | R 3/8" K | 3/4" - 16 UNF | 19 | 22 |
| GE HRK 06 AJ 10 | R 3/8" K | 7/8" - 14 UNF | 22 | 27 |
| GE HRK 08 AJ | R 1/2" K | 3/4" - 16 UNF | 27 | 32 |
| GE HRK 08 AJ 10 | R 1/2" K | 7/8" - 14 UNF | 22 | 27 |
| GE HRK 08 AJ 12 | R 1/2" K | 1.1/16" -12 UN | 27 | 32 |
| GE HRK 12 AJ 10 | R 3/4" K | 7/8" - 14 UNF | 27 | 27 |
| GE HRK 12 AJ | R 3/4" K | 1.1/16" -12 UN | 27 | 32 |
| GE HRK 12 AJ 14 | R 3/4" K | 1,3/16" -12 UN | 27 | 32 |
| GE HRK 12 AJ 16 | R 3/4" K | 1,5/16" -12 UN | 32 | 38 |
| GE HRK 16 AJ | R 1" K | 1,5/16" -12 UN | 36 | 38 |
| GE HRK 16 AJ 12 | R 1" K | 1.1/16" -12 UN | 36 | 38 |
| GE HRK 20 AJ | R 1,1/4" K | 1,5/8" -12 UN | 46 | 50 |
| GE HRK 24 AJ | R 1,1/2" K | 1,7/8" -12 UN | 54 | 55 |

SW, S1, S2 = širina ključa