

# GE HRK HJR

Uvrtni nastavci

**HANSA FLEX**

## Karakteristike

<b>Priključak 1</b>	BSP vanjski navoj, konusni
<b>Oblik brtve 1</b>	brtvljenje navoja
<b>Priključak 2</b>	BSP vanjski navoj, cilindrični
<b>Oblik brtve 2</b>	60° vanjski konus
<b>Izvedba</b>	Uvrtni nastavci
<b>Oblik izrade</b>	ravno
<b>Normirani priključak 2</b>	JIS B 8363
<b>Materijal</b>	Čelik
<b>Površinska zaštita</b>	galvanski premaz



## Artikli

Naziv	G1	G2	SW (mm)
GE HRK 02 HJR	R 1/8" K	G 1/8" - 28	14
GE HRK 04 HJR	R 1/4" K	G 1/4" - 19	19
GE HRK 06 HJR	R 3/8" K	G 3/8" - 19	22
GE HRK 08 HJR	R 1/2" K	G 1/2" - 14	27
GE HRK 12 HJR	R 3/4" K	G 3/4" - 14	37
GE HRK 16 HJR	R 1" K	G 1" - 11	41
GE HRK 20 HJR	R 1,1/4" K	G 1,1/4" - 11	50
GE HRK 24 HJR	R 1,1/2" K	G 1,1/2" - 11	55

SW = širina ključa