


Karakteristike

| | |
|---------------------------|--|
| Priključak 1 | UN/UNF vanjski navoji |
| Oblik brtve 1 | O prstenasta brtva na uvrtnom nastavku |
| Priključak 2 | NPSM navoji matice |
| Oblik brtve 2 | 60° vanjski konus |
| Izvedba | Uvrtni nastavci |
| Oblik izrade | ravno |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Artikli

| Naziv | G1 | G2 | SW (mm) | S1 | OR |
|---------------|----------------|---------------|------------|----|--------------|
| GE O 04 AN | 7/16" -20 UNF | 1/4" - 18 NPT | 14 | 18 | 8,92 x 1,83 |
| GE O 06 AN | 9/16" - 18 UNF | 3/8" - 18 NPT | 18 | 22 | 11,90 x 1,98 |
| GE O 06 AN 08 | 9/16" - 18 UNF | 1/2" - 14 NPT | 19 | 25 | 11,90 x 1,98 |
| GE O 08 AN | 3/4" - 16 UNF | 1/2" - 14 NPT | 22 | 25 | 16,36 x 2,20 |
| GE O 08 AN 12 | 3/4" - 16 UNF | 3/4" - 14 NPT | 25 | 32 | 16,36 x 2,20 |
| GE O 10 AN 06 | 7/8" -14 UNF | 3/8" - 18 NPT | 22 | 25 | 19,18 x 2,46 |
| GE O 10 AN 08 | 7/8" -14 UNF | 1/2" - 14 NPT | 25 | 25 | 19,18 x 2,46 |
| GE O 12 AN 08 | 1.1/16" -12 UN | 1/2" - 14 NPT | 32 | 25 | 23,47 x 2,95 |
| GE O 12 AN | 1.1/16" -12 UN | 3/4" - 14 NPT | 32 | 32 | 23,47 x 2,95 |
| GE O 16 AN | 1,5/16" -12 UN | 1" -11,5 NPT | 38 | 38 | 29,74 x 2,95 |

SW, S1, S2 = širina klučca