

GE O HJ VA

Uvrtni nastavci

HANSA FLEX

Karakteristike

Priključak 1	UN/UNF vanjski navoji
Oblik brtve 1	O prstenasta brtva na uvrtnom nastavku
Priključak 2	UN/UNF vanjski navoji
Oblik brtve 2	74° vanjski konus
Izvedba	Uvrtni nastavci
Oblik izrade	ravno
Materijal	Oplemenjeni čelik



Napomene uz narudžbu

Ulošci NBR ulošci brtve
FPM (Viton) na zahtjev

Artikli

Naziv	G1	G2	SW (mm)	OR
GE O 04 HJ VA	7/16" -20 UNF	7/16" -20 UNF	14	8,92 x 1,83
GE O 04 HJ 06 VA	7/16" -20 UNF	9/16" - 18 UNF	16	8,92 x 1,83
GE O 05 HJ 04 VA	1/2" -20 UNF	7/16" -20 UNF	16	10,52 x 1,83
GE O 05 HJ VA	1/2" -20 UNF	1/2" -20 UNF	16	10,52 x 1,83
GE O 05 HJ 06 VA	1/2" -20 UNF	9/16" - 18 UNF	16	10,52 x 1,83
GE O 06 HJ 04 VA	9/16" - 18 UNF	7/16" -20 UNF	17	11,90 x 1,98
GE O 06 HJ 08 VA	9/16" - 18 UNF	3/4" - 16 UNF	19	11,90 x 1,98
GE O 08 HJ 06 VA	3/4" - 16 UNF	9/16" - 18 UNF	22	16,36 x 2,20
GE O 08 HJ VA	3/4" - 16 UNF	3/4" - 16 UNF	22	16,36 x 2,20
GE O 08 HJ 12 VA	3/4" - 16 UNF	1.1/16" -12 UN	29	16,36 x 2,20
GE O 10 HJ 08 VA	7/8" -14 UNF	3/4" - 16 UNF	27	19,18 x 2,46
GE O 10 HJ VA	7/8" -14 UNF	7/8" - 14 UNF	27	19,18 x 2,46
GE O 12 HJ 08 VA	1.1/16" -12 UN	3/4" - 16 UNF	32	23,47 x 2,95
GE O 12 HJ VA	1.1/16" -12 UN	1.1/16" -12 UN	32	23,47 x 2,95
GE O 12 HJ 16 VA	1.1/16" -12 UN	1,5/16" -12 UN	36	23,47 x 2,95
GE O 16 HJ VA	1,5/16" -12 UN	1,5/16" -12 UN	38	29,74 x 2,95
GE O 16 HJ 20 VA	1,5/16" -12 UN	1,5/8" -12 UN	43	29,74 x 2,95
GE O 20 HJ VA	1,5/8" -12 UN	1,5/8" -12 UN	50	37,47 x 3,00
GE O 24 HJ VA	1,7/8" -12 UN	1,7/8" -12 UN	55	43,69 x 3,00

SW = širina ključa

Varijante proizvoda

GE O HJ Uvrtni nastavci, Čelik