



PHD 200

Pritisni podnožak za pletena crijeva

HANSA FLEX

Karakteristike

Vrsta podnoška	Ljušteni podnožak
prikladno za	2SN (HD 200, HD 200T, HF 200, HW 200, HDB 200) 1SC (KP 400) 4SP (HD 400)
Materijal	Čelik
Površinska zaštita	galvanski premaz



Napomena

Podnožak se dodjeljuje ovisno o tipu crijeva.

Artikli

Naziv	DN*	Veličina	Col	D1 (mm)	D3 (mm)	LF (mm)
PHD 204	5	3	3/16"	21	8,5	26,0
PHD 206	6	4	1/4"	22	11,4	30,0
PHD 208	8	5	5/16"	23	12,5	30,0
PHD 210	10	6	3/8"	26	14,5	31,0
PHD 213	12	8	1/2"	30	18,3	32,0
PHD 416	16	10	5/8"	33	21,7	38,0
PHD 220	19	12	3/4"	38	24,4	42,5
PHD 225	25	16	1"	46	30,5	51,0
PHD 232	31	20	1.1/4"	57	38,0	58,0
PHD 240	38	24	1.1/2"	65	44,3	62,0
PHD 250	51	32	2"	79	57,0	73,5
PHD 260	60	40	2.3/8"	84	67,1	79,0
PHD 276	76	48	3"	105	81,8	80,0

DN = nazivni promjer, nazivna širina