

Karakteristike

Područje primjene Visokotlačni uređaji za čišćenje

Temperatura min. -50 °C

Temperatura max. 135 °C

Materijal Guma

**Opis**

Sprječava prelamanje crijeva iza podnoška.

Artikli

Naziv	DN*	Col	Unutamji Ø (mm)	Duljina (mm)	Boja
GKS 06	6	1/4"	14,3	120	crna
GKS 08	8	5/16"	17,0	148	crna
GKS 08 BLAU	8	5/16"	17,0	148	plava
GKS 08 GELB	8	5/16"	17,0	148	žuta
GKS 08 GRAU	8	5/16"	17,0	148	siva
GKS 08 ORANGE	8	5/16"	17,0	148	narančasta
GKS 08 ROT	8	5/16"	17,0	148	crvena
GKS 10	10	3/8"	19,5	148	crna
GKS 10 BLAU	10	3/8"	19,5	148	plava
GKS 10 GELB	10	3/8"	19,5	148	žuta
GKS 10 GRAU	10	3/8"	19,5	148	siva
GKS 10 ORANGE	10	3/8"	19,5	148	narančasta
GKS 10 ROT	10	3/8"	19,5	148	crvena
GKS 13 BLAU	12	1/2"	23,9	148	plava
GKS 13 GRAU	12	1/2"	23,9	148	siva

DN = nazivni promjer, nazivna širina