

# TKM OV HB

Kolčak temperirane spojke bez ventila

**HANSA FLEX**

## Karakteristike

**Priključak 1** BSP vanjski navoj, cilindrični

**Oblik brtve 1** 60° unutarjni konus

**Materijal** Mjed



## Napomene uz narudžbu

Druge vrijednosti tlakova i temperature na upit.

## Artikli

| Naziv           | DN* | Navoj priključka | Dimenzija utikača (mm) | Radni tlak (bar) | SF skr.* | Temperatura mineralnog ulja min. (°C) | Temperatura mineralnog ulja max. (°C) | SW (mm) |
|-----------------|-----|------------------|------------------------|------------------|----------|---------------------------------------|---------------------------------------|---------|
| TKM 09 OV 06 HB | 6   | G 1/4" -19       | 9                      | 15,0             | 3        | -15                                   | 150                                   | 17      |
| TKM 09 OV 10 HB | 10  | G 3/8" -19       | 9                      | 15,0             | 3        | -15                                   | 150                                   | 19      |
| TKM 13 OV 06 HB | 6   | G 1/4" -19       | 13                     | 15,0             | 3        | -15                                   | 150                                   | 22      |
| TKM 13 OV 10 HB | 10  | G 3/8" -19       | 13                     | 15,0             | 3        | -15                                   | 150                                   | 22      |
| TKM 19 OV 13 HB | 12  | G 1/2" -14       | 19                     | 15,0             | 3        | -15                                   | 150                                   | 30      |
| TKM 19 OV 20 HB | 19  | G 3/4" -14       | 19                     | 15,0             | 3        | -15                                   | 150                                   | 30      |

DN = nazivni promjer, nazivna širina – SF spoj. = spojeni faktor sigurnosti – SW = širina ključa