

TKS OV HB

Utikač temperirane spojke bez ventila

HANSA FLEX

Karakteristike

Priključak 1 BSP vanjski navoj, cilindrični

Oblik brtve 1 60° unutarjni konus

Materijal Mjed



Napomene uz narudžbu

Druge vrijednosti tlakova i temperature na upit.

Artikli

Naziv	DN*	Navoj priključka	Dimenzija utikača (mm)	Radni tlak (bar)	SF skr.*	Temperatura mineralnog ulja min. (°C)	Temperatura mineralnog ulja max. (°C)	SW (mm)
TKS 09 OV 02 HB	2	G 1/8" - 28	9	15,0	3	-15	150	11
TKS 09 OV 06 HB	6	G 1/4" -19	9	15,0	3	-15	150	15
TKS 09 OV 10 HB	10	G 3/8" -19	9	15,0	3	-15	150	17
TKS 13 OV 06 HB	6	G 1/4" -19	13	15,0	3	-15	150	15
TKS 13 OV 10 HB	10	G 3/8" -19	13	15,0	3	-15	150	17
TKS 13 OV 13 HB	12	G 1/2" -14	13	15,0	3	-15	150	22
TKS 19 OV 13 HB	12	G 1/2" -14	19	15,0	3	-15	150	22
TKS 19 OV 20 HB	19	G 3/4" -14	19	15,0	3	-15	150	27

DN = nazivni promjer, nazivna širina – SF spoj. = spojeni faktor sigurnosti – SW = širina ključa