

TKS OV MM ND

Utikač temperirane spojke bez ventila

HANSA FLEX

Karakteristike

Priključak 1 Priključak crijeva

Materijal Mjed



Napomene uz narudžbu

Druge vrijednosti tlakova i temperature na upit.

Artikl

| Naziv | DN* | Priključak crijeva (mm) | Dimenzija utikača (mm) | Radni tlak (bar) | SF skr.* | Temperatura mineralnog ulja min. (°C) | Temperatura mineralnog ulja max. (°C) |
|--------------------|-----|-------------------------|------------------------|------------------|----------|---------------------------------------|---------------------------------------|
| TKS 09 OV 06 MM ND | 6 | 6 | 9 | 15,0 | 3 | -15 | 150 |
| TKS 09 OV 10 MM ND | 10 | 10 | 9 | 15,0 | 3 | -15 | 150 |
| TKS 13 OV 10 MM ND | 10 | 10 | 13 | 15,0 | 3 | -15 | 150 |
| TKS 13 OV 13 MM ND | 12 | 13 | 13 | 15,0 | 3 | -15 | 150 |
| TKS 19 OV 16 MM ND | 16 | 16 | 19 | 15,0 | 3 | -15 | 150 |
| TKS 19 OV 19 MM ND | 19 | 19 | 19 | 15,0 | 3 | -15 | 150 |

DN = nazivni promjer, nazivna širina – SF spoj. = spojeni faktor sigurnosti