


ND B

Utična nazuvica, RGN

HANSA FLEX

Karakteristike

Priključak 1	Ušica za metričke šuplje vijke
Oblik brtve 1	Brtvljenje s bakrenim prstenom
Priključak 2	Priključak crijeva
Kratice	RGN
Norma	DIN 7642
Materijal	Čelik
Površinska zaštita	galvanski premaz



Napomena

Neoštećene nazuvice možete upotrijebiti ponovno.

Artikl

Naziv	DN	Veličina	Col	D1 (mm)	za šuplji vijak	L1 (mm)
ND 06 B 02	6	4	1/4"	8,1	M 8	36,0
ND 06 B 04	6	4	1/4"	10,1	M 10	38,0
ND 06 B	6	4	1/4"	12,1	M 12	40,0
ND 06 B 08	6	4	1/4"	14,1	M 14	42,0
ND 10 B 06	10	6	3/8"	12,1	M 12	44,0
ND 10 B 08	10	6	3/8"	14,1	M 14	47,0
ND 10 B	10	6	3/8"	16,1	M 16	49,0
ND 13 B 08	12	8	1/2"	14,1	M 14	51,0
ND 13 B 16	12	8	1/2"	22,1	M 22	58,0
ND 16 B	16	10	5/8"	22,1	M 22	68,0

Pribor

ND ASR GE, RO, BL Granični prsten za utičnu nazuvicu