

ND FL / ND FS

Utična nazuvica, BEL / BES

HANSA FLEX

Karakteristike

Priključak 1	Nastavci cijevi
Oblik brtve 1	Spoj za narezni prsten
Kratika	BEL / BES
Norma	ISO 8434-1
Materijal	Čelik
Površinska zaštita	galvanski premaz



Napomena

Neoštećene nazuvice možete upotrijebiti ponovno.

Narezni prsten potrebno je završno montirati na kaljenom nastavku za predmontažu (VOM...).

Ne koristite kod novih konstrukcija; preporučujemo za ND...FL: ND...AOL.

Artikli

Naziv	DN	Veličina	Col	Serija	D2 (mm)	L1 (mm)
ND 06 FL 04	6	4	1/4"	L	6,0	44,0
ND 06 FL	6	4	1/4"	L	8,0	44,0
ND 10 FL 08	10	6	3/8"	L	10,0	49,0
ND 10 FL	10	6	3/8"	L	12,0	49,0
ND 13 FL 10	12	8	1/2"	L	12,0	54,0
ND 13 FL	12	8	1/2"	L	15,0	55,0
ND 16 FL	16	10	5/8"	L	18,0	67,0
ND 20 FL	19	12	3/4"	L	22,0	69,0
ND 06 FS	6	4	1/4"	S	10,0	-

Pribor

ND ASR GE, RO, BL Granični prsten za utičnu nazuvicu

Dodatni elementi

VOM Nastavci za predmontažu