

Karakteristike

Priključak 1	BSP vanjski navoj, cilindrični
Oblik brtve 1	60° unutarnji konus
Kratika	AGR
Norma	ISO 8434-6 BS 5200
Opseg isporuke	Pritisna nazuvica + pritisni podnožak
Materijal	Čelik
Površinska zaštita	galvanski premaz



Artikli

Naziv	DN	Veličina	Col	G1	L1 (mm)	S1
PAY 306 HB	6	4	1/4"	G 1/4" - 19	64,0	17
PAY 308 HB 10	8	5	5/16"	G 3/8" - 19	64,0	22
PAY 310 HB	10	6	3/8"	G 3/8" - 19	71,0	22
PAY 310 HB 13	10	6	3/8"	G 1/2" -14	76,0	22
PAY 313 HB	12	8	1/2"	G 1/2" -14	79,0	24
PAY 316 HB 20	16	10	5/8"	G 3/4" -14	92,0	32
PAY 320 HB	19	12	3/4"	G 3/4" -14	92,0	32
PAY 320 HB 25	19	12	3/4"	G 1" -11	100,0	36
PAY 325 HB	25	16	1"	G 1" -11	100,0	36
PAY 325 HB 32	25	16	1"	G 1,1/4" - 11	103,0	50
PAY 332 HB 40	31	20	1.1/4"	G 1,1/2" - 11	118,0	55