


PN AJF 90

Pritisna nazuvica, ORFS W90°

HANSA FLEX

Karakteristike

Područje primjene	Pritisna nazuvica za HD 100- do HD 400-, KP-, TE crijeva
Priključak 1	UN/UNF navoji matice
Oblik brtve 1	plosnato brtvljenje
Kratica	ORFS
Norma	ISO 8434- 3
Materijal	Čelik
Površinska zaštita	galvanski premaz



Napomena

Odgovarajući podnožak molimo da odaberete prema tipu crijeva.

Artikli

Naziv	DN	Veličina	Col	Radni tlak (bar)	G1	L1 (mm)	L2 (mm)	S1
PN 06 AJF 90	6	4	1/4"	413,0	9/16" - 18 UNF	55,0	26,5	17
PN 06 AJF 90 L21	6	4	1/4"	413,0	9/16" - 18 UNF	55,0	21,0	17
PN 06 AJF 90 L58	6	4	1/4"	413,0	9/16" - 18 UNF	55,0	58,0	17
PN 06 AJF 10 90	6	4	1/4"	413,0	11/16" - 16 UN	55,0	28,0	22
PN 08 AJF 10 90	8	5	5/16"	413,0	11/16" - 16 UN	58,0	28,0	22
PN 08 AJF 10 90 L23	8	5	5/16"	413,0	11/16" - 16 UN	58,0	23,0	22
PN 10 AJF 90	10	6	3/8"	413,0	11/16" - 16 UN	64,0	32,0	22
PN 10 AJF 90 L23	10	6	3/8"	413,0	11/16" - 16 UN	64,0	23,0	22
PN 10 AJF 90 L 69	10	6	3/8"	413,0	11/16" - 16 UN	64,0	69,0	22
PN 10 AJF 13 90	10	6	3/8"	413,0	13/16" - 16 UN	64,0	33,0	24
PN 13 AJF 10 90 L30	12	8	1/2"	413,0	11/16" - 16 UN	72,5	30,0	22
PN 13 AJF 90	12	8	1/2"	413,0	13/16" - 16 UN	72,5	37,0	24
PN 13 AJF 90 L29	12	8	1/2"	413,0	13/16" - 16 UN	72,5	29,0	24
PN 13 AJF 90 L82	12	8	1/2"	413,0	13/16" - 16 UN	72,5	82,0	24
PN 13 AJF 16 90	12	8	1/2"	413,0	1" -14 UNS	72,5	41,0	30
PN 13 AJF 20 90	12	8	1/2"	413,0	1,3/16" -12 UN	71,5	43,5	36
PN 13 AJF 20 90 L38	12	8	1/2"	413,0	1,3/16" -12 UN	72,5	38,0	36
PN 16 AJF 90	16	10	5/8"	413,0	1" -14 UNS	88,0	47,5	30
PN 16 AJF 90 L32	16	10	5/8"	413,0	1" -14 UNS	88,0	32,0	30
PN 16 AJF 90 L94	16	10	5/8"	413,0	1" -14 UNS	88,0	94,0	30
PN 16 AJF 20 90	16	10	5/8"	413,0	1,3/16" -12 UN	89,5	49,0	36
PN 20 AJF 90	19	12	3/4"	413,0	1,3/16" -12 UN	99,5	52,0	36
PN 20 AJF 90 L48	19	12	3/4"	413,0	1,3/16" -12 UN	99,5	48,0	36
PN 20 AJF 90 L96	19	12	3/4"	413,0	1,3/16" -12 UN	99,5	96,0	36
PN 20 AJF 25 90	19	12	3/4"	413,0	1,7/16" -12 UN	98,5	56,0	41
PN 25 AJF 20 90 L51	25	16	1"	413,0	1,3/16" -12 UN	127,0	51,0	36
PN 25 AJF 90	25	16	1"	413,0	1,7/16" -12 UN	127,0	63,5	41
PN 25 AJF 90 L56	25	16	1"	413,0	1,7/16" -12 UN	127,0	56,0	41
PN 25 AJF 90 L114	25	16	1"	413,0	1,7/16" -12 UN	127,0	114,0	41
PN 32 AJF 90	31	20	1.1/4"	275,0	1.11/16" -12 UN	151,5	76,0	50
PN 32 AJF 90 L129	31	20	1.1/4"	275,0	1.11/16" -12 UN	151,5	129,0	50
PN 40 AJF 90	38	24	1.1/2"	275,0	2" -12 UN	176,5	89,0	60
PN 40 AJF 90 L146	38	24	1.1/2"	275,0	2" -12 UN	176,5	146,0	60