


PN BR

Pritisna nazuvica, RGN

HANSA FLEX

Karakteristike

Područje primjene	Pritisna nazuvica za HD 100- do HD 400-, KP-, TE crijeva
Priključak 1	Ušica za colne šuplje vijke
Oblik brtve 1	Brtvljenje s bakrenim prstenom
Kratice	RNR
Materijal	Čelik
Površinska zaštita	galvanski premaz



Napomena

Odgovarajući podnožak molimo da odaberete prema tipu crijeva.

Artikli

Naziv	DN	Veličina	Col	Radni tlak (bar)	D1 (mm)	za šuplji vijak	L1 (mm)
PN 04 BR	5	3	3/16"	200,0	10,1	R 1/8"	42,5
PN 04 BR 06	5	3	3/16"	200,0	13,2	R 1/4"	43,5
PN 06 BR 02	6	4	1/4"	200,0	10,1	R 1/8"	48,5
PN 06 BR	6	4	1/4"	200,0	13,2	R 1/4"	49,5
PN 06 BR 10	6	4	1/4"	200,0	16,7	R 3/8"	52,5
PN 08 BR 06	8	5	5/16"	200,0	13,2	R 1/4"	49,5
PN 08 BR 10	8	5	5/16"	200,0	16,7	R 3/8"	52,5
PN 10 BR 06	10	6	3/8"	200,0	13,2	R 1/4"	58,5
PN 10 BR	10	6	3/8"	200,0	16,7	R 3/8"	54,0
PN 10 BR 13	10	6	3/8"	200,0	21,0	R 1/2"	59,5
PN 13 BR 10	12	8	1/2"	200,0	16,7	R 3/8"	58,0
PN 13 BR	12	8	1/2"	200,0	21,0	R 1/2"	60,5
PN 13 BR 16	12	8	1/2"	200,0	23,0	R 5/8"	63,0
PN 16 BR	16	10	5/8"	200,0	23,0	R 5/8"	67,5
PN 16 BR 20	16	10	5/8"	200,0	26,5	R 3/4"	72,0
PN 20 BR	19	12	3/4"	200,0	26,5	R 3/4"	78,5
PN 20 BR 25	19	12	3/4"	200,0	33,3	R 1"	87,0
PN 25 BR	25	16	1"	200,0	33,3	R 1"	95,0