


PN FL 90

Pritisna nazuvica, BEL W90°

HANSA FLEX

Karakteristike

Područje primjene	Pritisna nazuvica za HD 100- do HD 400-, KP-, TE cijeva
Priključak 1	Nastavci cijevi
Oblik brtve 1	Spoj za narezni prsten
Kratice	BEL
Norma	ISO 8434-1
Serijska	lagana
Materijal	Čelik
Površinska zaštita	galvanski premaz



Napomena

Narezni prsten potrebno je završno montirati na kaljenom nastavku za predmontažu (VOM...).

Odgovarajući podnožak molimo da odaberete prema tipu cijeva.

Ne koristiti kod novih konstrukcija; preporučujemo: PN...AOL...90.

Artikli

Naziv	DN	Veličina	Col	Radni tlak (bar)	D2 (mm)	L1 (mm)	L2 (mm)
PN 04 FL 90	5	3	3/16"	250,0	6,0	47,5	41,5
PN 06 FL 04 90	6	4	1/4"	250,0	6,0	56,5	42,5
PN 06 FL 90	6	4	1/4"	250,0	8,0	56,5	43,5
PN 08 FL 06 90	8	5	5/16"	250,0	8,0	56,5	43,5
PN 08 FL 90	8	5	5/16"	250,0	10,0	58,5	44,0
PN 10 FL 08 90	10	6	3/8"	250,0	10,0	61,5	53,5
PN 10 FL 90	10	6	3/8"	250,0	12,0	62,0	52,5
PN 10 FL 13 90	10	6	3/8"	250,0	15,0	77,5	48,0
PN 13 FL 10 90	12	8	1/2"	250,0	12,0	62,0	52,5
PN 13 FL 90	12	8	1/2"	250,0	15,0	72,5	55,0
PN 13 FL 16 90	12	8	1/2"	160,0	18,0	72,5	58,5
PN 16 FL 90	16	10	5/8"	160,0	18,0	83,0	70,0
PN 16 FL 20 90	16	10	5/8"	160,0	22,0	83,0	74,0
PN 20 FL 16 90	19	12	3/4"	160,0	18,0	88,0	70,0
PN 20 FL 90	19	12	3/4"	160,0	22,0	100,0	73,5
PN 25 FL 90	25	16	1"	100,0	28,0	127,5	84,5
PN 32 FL 90	31	20	1.1/4"	100,0	35,0	149,5	106,0
PN 40 FL 90	38	24	1.1/2"	100,0	42,0	167,0	99,0

Varijante proizvoda

PN FL 90 VA Pritisna nazuvica, BEL W90°, Oplemenjeni čelik

Dodatni elementi

VOM Nastavci za predmontažu