


PN FL 90 VA

Pritisna nazuvica, BEL W90°

HANSA FLEX

Karakteristike

Područje primjene	Pritisna nazuvica za HD 100- do HD 400-, KP-, TE crijeva
Priključak 1	Nastavci cijevi
Oblik brtve 1	Spoj za narezni prsten
Kratica	BEL
Norma	ISO 8434-1
Serijska	lagana
Materijal	Oplemenjeni čelik



Napomena

Narezni prsten potrebno je završno montirati na kaljenom nastavku za predmontažu (VOM...).

Odgovarajući podnožak molimo da odaberete prema tipu crijeva.

Ne koristiti kod novih konstrukcija; preporučujemo: PN...AOL...90 VA.

Artikli

Naziv	DN	Veličina	Col	Radni tlak (bar)	D2 (mm)	L1 (mm)	L2 (mm)
PN 06 FL 04 90 VA	6	4	1/4"	250,0	6,0	62,3	32,5
PN 06 FL 90 VA	6	4	1/4"	250,0	8,0	68,3	37,0
PN 06 FL 08 90 VA	6	4	1/4"	250,0	10,0	72,8	40,0
PN 08 FL 90 VA	8	5	5/16"	250,0	10,0	70,8	41,5
PN 08 FL 10 90 VA	8	5	5/16"	250,0	12,0	77,8	45,0
PN 10 FL 08 90 VA	10	6	3/8"	250,0	10,0	70,8	41,5
PN 10 FL 90 VA	10	6	3/8"	250,0	12,0	77,8	45,0
PN 13 FL 90 VA	12	8	1/2"	250,0	15,0	84,8	49,0
PN 16 FL 90 VA	16	10	5/8"	-	18,0	93,0	65,0
PN 20 FL 90 VA	19	12	3/4"	-	22,0	112,0	75,5
PN 25 FL 90 VA	25	16	1"	100,0	28,0	127,5	98,0
PN 32 FL 90 VA	31	20	1.1/4"	100,0	35,0	174,0	127,0
PN 40 FL 90 VA	38	24	1.1/2"	100,0	42,0	174,0	127,0

Varijante proizvoda

PN FL 90 Pritisna nazuvica, BEL W90°, Čelik

Dodatni elementi

VOM Nastavci za predmontažu