

PN FS 45 VA

Pritisna nazuvica, BES W45°

HANSA FLEX

Karakteristike

Područje primjene	Pritisna nazuvica za HD 100- do HD 400-, KP-, TE cijeva
Priključak 1	Nastavci cijevi
Oblik brtve 1	Spoj za narezni prsten
Kratika	BES
Norma	ISO 8434-1
Serijska	teška
Materijal	Oplemenjeni čelik



Napomena

Narezni prsten potrebno je završno montirati na kaljenom nastavku za predmontažu (VOM...).

Odgovarajući podnožak molimo da odaberete prema tipu cijeva.

Ne koristiti kod novih konstrukcija; preporučujemo: PN...AOS...45 VA.

Artikli

Naziv	DN	Veličina	Col	D2 (mm)	L2 (mm)
PN 06 FS 03 45 VA	6	4	1/4"	6,0	22,0
PN 06 FS 04 45 VA	6	4	1/4"	8,0	22,0
PN 06 FS 45 VA	6	4	1/4"	10,0	22,5
PN 08 FS 06 45 VA	8	5	5/16"	10,0	25,0
PN 08 FS 45 VA	8	5	5/16"	12,0	24,0
PN 10 FS 06 45 VA	10	6	3/8"	10,0	25,0
PN 10 FS 08 45 VA	10	6	3/8"	12,0	45,0
PN 10 FS 45 VA	10	6	3/8"	14,0	-
PN 13 FS 45 VA	12	8	1/2"	16,0	32,0
PN 16 FS 45 VA	16	10	5/8"	20,0	31,0
PN 20 FS 45 VA	19	12	3/4"	25,0	42,0
PN 25 FS 45 VA	25	16	1"	30,0	-
PN 32 FS 45 VA	31	20	1.1/4"	38,0	-

Varijante proizvoda

PN FS 45 Pritisna nazuvica, BES W45°, Čelik