


PN FS 90

Pritisna nazuvica, BES W90°

HANSA FLEX

Karakteristike

Područje primjene	Pritisna nazuvica za HD 100- do HD 400-, KP-, TE crijeva
Priključak 1	Nastavci cijevi
Oblik brtve 1	Spoj za narezni prsten
Kratica	BES
Norma	ISO 8434-1
Serijska	teška
Materijal	Čelik
Površinska zaštita	galvanski premaz



Napomena

Narezni prsten potrebno je završno montirati na kaljenom nastavku za predmontažu (VOM...).

Odgovarajući podnožak molimo da odaberete prema tipu crijeva.

Ne koristiti kod novih konstrukcija; preporučujemo: PN...AOS...90.

Artikli

Naziv	DN	Veličina	Col	Radni tlak (bar)	D2 (mm)	L1 (mm)	L2 (mm)
PN 04 FS 90	5	3	3/16"	630,0	8,0	59,0	37,0
PN 06 FS 04 90	6	4	1/4"	630,0	8,0	56,5	43,5
PN 06 FS 90	6	4	1/4"	630,0	10,0	56,5	44,5
PN 06 FS 08 90	6	4	1/4"	630,0	12,0	56,5	44,5
PN 08 FS 90	8	5	5/16"	630,0	12,0	57,0	46,5
PN 10 FS 90	10	6	3/8"	630,0	14,0	58,5	60,5
PN 13 FS 08 90	12	8	1/2"	400,0	12,0	58,5	46,5
PN 13 FS 10 90	12	8	1/2"	400,0	14,0	70,5	61,5
PN 13 FS 90	12	8	1/2"	400,0	16,0	71,5	63,5
PN 16 FS 13 90	16	10	5/8"	400,0	16,0	76,0	63,5
PN 16 FS 90	16	10	5/8"	400,0	20,0	83,0	80,5
PN 20 FS 16 90	19	12	3/4"	400,0	20,0	100,0	80,0
PN 20 FS 90	19	12	3/4"	400,0	25,0	100,0	85,5
PN 25 FS 20 90	25	16	1"	250,0	25,0	127,5	94,5
PN 25 FS 90	25	16	1"	250,0	30,0	127,5	99,5
PN 32 FS 25 90	31	20	1.1/4"	250,0	30,0	135,0	99,5
PN 32 FS 90	31	20	1.1/4"	250,0	38,0	156,0	105,0
PN 40 FS 32 90	38	24	1.1/2"	250,0	38,0	159,5	105,0

Varijante proizvoda

PN FS 90 VA Pritisna nazuvica, BES W90°, Oplemenjeni čelik