

T IR HJ

Spojni nastavak, T oblik

HANSA FLEX

Karakteristike

| | |
|--------------------|----------------------------------|
| Priključak 1 | BSP unutarnji navoj, cilindrični |
| Oblik brtve 1 | Profil A |
| Priključak 2 + 3 | UN/UNF vanjski navoji |
| Oblik brtve 2 + 3 | 74° vanjski konus |
| Izvedba | Spojni nastavci |
| Oblik izrade | T oblik |
| Materijal | Čelik |
| Površinska zaštita | galvanski premaz |



Artikli

| Naziv | G1 | G2 + G3 | SW (mm) |
|---------------|-------------|----------------|------------|
| T IR 02 HJ 05 | G 1/8" - 28 | 1/2" -20 UNF | 14 |
| T IR 04 HJ | G 1/4" - 19 | 9/16" - 18 UNF | 19 |
| T IR 04 HJ 05 | G 1/4" - 19 | 1/2" -20 UNF | 19 |
| T IR 04 HJ 06 | G 1/4" - 19 | 9/16" - 18 UNF | 19 |
| T IR 04 HJ 08 | G 1/4" - 19 | 3/4" - 16 UNF | 22 |
| T IR 06 HJ 04 | G 3/8" - 19 | 7/16" -20 UNF | 22 |
| T IR 06 HJ | G 3/8" - 19 | 9/16" - 18 UNF | 22 |
| T IR 06 HJ 08 | G 3/8" - 19 | 3/4" - 16 UNF | 22 |
| T IR 08 HJ | G 1/2" -14 | 3/4" - 16 UNF | 27 |
| T IR 08 HJ 10 | G 1/2" -14 | 7/8" - 14 UNF | 27 |
| T IR 08 HJ 12 | G 1/2" -14 | 1.1/16" -12 UN | 33 |
| T IR 12 HJ | G 3/4" -14 | 1.1/16" -12 UN | 33 |
| T IR 16 HJ | G 1" -11 | 1,5/16" -12 UN | 41 |

SW = širina ključa