

# T IR HJ

Spojni nastavak, T oblik

**HANSA FLEX**

## Karakteristike

|                    |                                  |
|--------------------|----------------------------------|
| Priključak 1       | BSP unutarnji navoj, cilindrični |
| Oblik brtve 1      | Profil A                         |
| Priključak 2 + 3   | UN/UNF vanjski navoji            |
| Oblik brtve 2 + 3  | 74° vanjski konus                |
| Izvedba            | Spojni nastavci                  |
| Oblik izrade       | T oblik                          |
| Materijal          | Čelik                            |
| Površinska zaštita | galvanski premaz                 |



## Artikli

| Naziv         | G1          | G2 + G3        | SW<br>(mm) |
|---------------|-------------|----------------|------------|
| T IR 02 HJ 05 | G 1/8" - 28 | 1/2" -20 UNF   | 14         |
| T IR 04 HJ    | G 1/4" - 19 | 9/16" - 18 UNF | 19         |
| T IR 04 HJ 05 | G 1/4" - 19 | 1/2" -20 UNF   | 19         |
| T IR 04 HJ 06 | G 1/4" - 19 | 9/16" - 18 UNF | 19         |
| T IR 04 HJ 08 | G 1/4" - 19 | 3/4" - 16 UNF  | 22         |
| T IR 06 HJ 04 | G 3/8" - 19 | 7/16" -20 UNF  | 22         |
| T IR 06 HJ    | G 3/8" - 19 | 9/16" - 18 UNF | 22         |
| T IR 06 HJ 08 | G 3/8" - 19 | 3/4" - 16 UNF  | 22         |
| T IR 08 HJ    | G 1/2" -14  | 3/4" - 16 UNF  | 27         |
| T IR 08 HJ 10 | G 1/2" -14  | 7/8" - 14 UNF  | 27         |
| T IR 08 HJ 12 | G 1/2" -14  | 1.1/16" -12 UN | 33         |
| T IR 12 HJ    | G 3/4" -14  | 1.1/16" -12 UN | 33         |
| T IR 16 HJ    | G 1" -11    | 1,5/16" -12 UN | 41         |

SW = širina ključa