

FLD R N

Ravni brtveni prsten za vatrogasnu spojku

HANSA FLEX

Karakteristike

Izvedba	Ravna brtva za fiksnu spojku s unutrašnjim navojem
Materijal	Nitril-kaučuk crni



Artikli

Naziv	za navoje	Ø d1 (mm)	Ø d2 (mm)	S (mm)
FLD R 1/2 N	G 1/2"	17	22	2
FLD R 3/4 N	G 3/4"	18	27	2
FLD R 1 N	G 1"	20	33	3
FLD R 1 1/2 N	G 1,1/2"	39	48	3
FLD R1 1/4 N	G 1,1/4"	33	42	3
FLD R 2 N	G 2"	47	60	3
FLD R 2 1/2 N	G 2.1/2"	66	76	3
FLD R 3 N	G 3"	76	88	3
FLD R 4 N	G 4"	102	113	3
FLD R 4 1/2 N	G 4.1/2"	105	126	3
FLD R 5 N	G 5"	122	140	4

Varijante proizvoda

FLD R N W	Ravni brtveni prsten za vatrogasnu spojku, Nitril bijeli
FLD R T	Ravni brtveni prsten za vatrogasnu spojku, PTFE

je rezervni dio uz sljedeće proizvode

FK KG IR AL	Fiksna spojka za vatrogasne spojke
FK KG IR MG	Fiksna spojka za vatrogasne spojke