

FLD R N W

Ravni brtveni prsten za vatrogasnu spojku

HANSA FLEX

Karakteristike

| | |
|------------------|--|
| Izvedba | Ravna brtva za fiksnu spojku s unutrašnjim navojem |
| Materijal | Nitril bijeli |



Artikli

| Naziv | za navoje | Ø d1 (mm) | Ø d2 (mm) | S (mm) |
|-----------------|-----------|--------------|--------------|-----------|
| FLD R 1 N W | G 1" | 20 | 33 | 3 |
| FLD R 1 1/4 N W | G 1,1/4" | 33 | 42 | 3 |
| FLD R 1 1/2 N W | G 1,1/2" | 39 | 48 | 3 |
| FLD R 2 N W | G 2" | 47 | 60 | 3 |
| FLD R 2 1/2 N W | G 2.1/2" | 66 | 76 | 3 |
| FLD R 3 N W | G 3" | 76 | 88 | 3 |
| FLD R 4 N W | G 4" | 102 | 113 | 3 |
| FLD R 4 1/2 N W | G 4.1/2" | 105 | 126 | 3 |
| FLD R 5 N W | G 5" | 122 | 140 | 4 |

Varijante proizvoda

FLD R N

FLD R T

je rezervni dio uz sljedeće proizvode

| | |
|-------------|------------------------------------|
| FK KG IR AL | Fiksna spojka za vatrogasne spojke |
| FK KG IR MG | Fiksna spojka za vatrogasne spojke |