

# FLD R T

Ravni brtveni prsten za vatrogasnu spojku

**HANSA FLEX**

## Karakteristike

|           |  |
|-----------|--|
| Izvedba   | Ravna brtva za fiksnu spojku s unutrašnjim navojem |
| Materijal | PTFE   |



## Artikli

| Naziv         | za navoje | Ø d1<br>(mm) | Ø d2<br>(mm) | S<br>(mm) |
|---------------|-----------|--------------|--------------|-----------|
| FLD R 1 T     | G 1"      | 20           | 33           | 2         |
| FLD R 1 1/4 T | G 1,1/4"  | 33           | 42           | 2         |
| FLD R 1 1/2 T | G 1,1/2"  | 39           | 48           | 2         |
| FLD R 2 T     | G 2"      | 47           | 60           | 2         |
| FLD R 2 1/2 T | G 2.1/2"  | 66           | 76           | 2         |
| FLD R 3 T     | G 3"      | 76           | 88           | 2         |
| FLD R 4 T     | G 4"      | 102          | 113          | 2         |
| FLD R 4 1/2 T | G 4.1/2"  | 105          | 126          | 2         |
| FLD R 5 T     | G 5"      | 122          | 140          | 2         |

## Varijante proizvoda

FLD R N  
FLD R N W

## je rezervni dio uz sljedeće proizvode

|             |                                    |
|-------------|------------------------------------|
| FK KG IR AL | Fiksna spojka za vatrogasne spojke |
| FK KG IR MG | Fiksna spojka za vatrogasne spojke |