

Karakteristike

Priključak 1 BSP vanjski navoj, cilindrični

Priključak 2 Priključak crijeva

Materijal Mjed



Artikli

Naziv	Navoj priključka	za crijevo unutrašnjeg promjera (mm)	SW (mm)	Radni tlak bari
T 184 M	G 1/8" - 28	4	14	PN 16
T 186 M	G 1/8" - 28	6	14	PN 16
T 189 M	G 1/8" - 28	9	14	PN 16
T 144 M	G 1/4" -19	4	17	PN 16
T 146 M	G 1/4" -19	6	17	PN 16
T 149 M	G 1/4" -19	9	17	PN 16
T 1413 M	G 1/4" -19	13	17	PN 16
T 386 M	G 3/8" -19	6	19	PN 16
T 389 M	G 3/8" -19	9	19	PN 16
T 3813 M	G 3/8" -19	13	19	PN 16
T 126 M	G 1/2" -14	6	24	PN 16
T 129 M	G 1/2" -14	9	24	PN 16
T 1213 M	G 1/2" -14	13	24	PN 16
T 1219 M	G 1/2" -14	19	24	PN 16
T 349 M	G 3/4" -14	9	27	PN 16
T 3413 M	G 3/4" -14	13	32	PN 16
T 3419 M	G 3/4" -14	19	32	PN 16
T 1019 M	G 1" -11	19	26	PN 16
T 1025 M	G 1" -11	25	38	PN 16

SW = širina ključa