

Karakteristike

Priključak 1 + 2	BSP unutarnji navoj, cilindrični
Temperatura min.	0 °C
Temperatura max.	120 °C
Materijal	Mjed OT 58, ručka od čelika



Napomena

Podaci o tlaku vrijede za temperaturu 0 °C do + 25 °C; kod više temperature potrebno je uzeti u obzir smanjenje tlaka.

Napomene uz narudžbu

Druge vrijednosti tlakova i temperature na upit.

Artikli

Naziv	DN*	Veličina	Radni tlak (bar)	G1 + G2	L (mm)
MF 06 MG	6	4	16,0	G 1/4" - 19	33
MF 10 MG	10	6	16,0	G 3/8" - 19	41
MF 13 MG	12	8	16,0	G 1/2" -14	36
MF 20 MG	19	12	16,0	G 3/4" -14	39
MF 25 MG	25	16	16,0	G 1" -11	43
MF 32 MG	31	20	16,0	G 1,1/4" - 11	48
MF 40 MG	38	24	16,0	G 1,1/2" - 11	52
MF 50 MG	51	32	16,0	G 2" -11	57
MF 65 MG	60	40	16,0	G 2,1/2" - 11	65
MF 75 MG	76	48	16,0	G 3" -11	75
MF 100 MG	100	64	16,0	G 4" -11	84

DN = nazivni promjer, nazivna širina – G1 + G2 = navoji priključaka 1+2

Varijante proizvoda

MF VA Zasuni s kolčakom, Oplemenjeni čelik