

# 2 OK


## 2-ušna stezaljka

### Karakteristike

**Područje primjene** Pričvršćenja crijeva u području niskog tlaka

**Materijal** Čelik

**Površinska zaštita** galvanski premaz



### Artikli

| Naziv      | Područje zatezanja (mm) | Širina trake (mm) |
|------------|-------------------------|-------------------|
| 2 OK 5-7   | 5 - 7                   | 6,0               |
| 2 OK 7-9   | 7 - 9                   | 6,0               |
| 2 OK 9-11  | 9 - 11                  | 6,5               |
| 2 OK 11-13 | 11 - 13                 | 6,5               |
| 2 OK 13-15 | 13 - 15                 | 7,0               |
| 2 OK 14-17 | 14 - 17                 | 7,0               |
| 2 OK 15-18 | 15 - 18                 | 7,5               |
| 2 OK 17-20 | 17 - 20                 | 7,5               |
| 2 OK 18-21 | 18 - 21                 | 8,0               |
| 2 OK 20-23 | 20 - 23                 | 8,0               |
| 2 OK 22-25 | 22 - 25                 | 8,5               |
| 2 OK 23-27 | 23 - 27                 | 8,5               |
| 2 OK 25-28 | 25 - 28                 | 9,0               |
| 2 OK 28-31 | 28 - 31                 | 9,0               |
| 2 OK 31-34 | 31 - 34                 | 9,5               |
| 2 OK 34-37 | 34 - 37                 | 9,5               |
| 2 OK 37-40 | 37 - 40                 | 10,0              |
| 2 OK 40-43 | 40 - 43                 | 10,0              |
| 2 OK 43-46 | 43 - 46                 | 10,0              |

### Varijante proizvoda

2 OK VC 2-ušna stezaljka, sjajno pocinčana

2 OK VA 2-ušna stezaljka, Oplemenjeni čelik