

NRS W4 (15 mm)

Obujmica držača

HANSA FLEX

Karakteristike

Područje primjene za pričvršćivanje cijevi, crijeva i kabela

Izvedba Cijevna obujmica

Dodatak kod izvedbe s gumenim profilom

Norma DIN 3016

Materijal Krom-nikal čelik (1.4301)



Artikli

Naziv	najmanji Ø (mm)	Širina trake (mm)	Provrt Ø (mm)
NRS 05-15 W4	5	15,0	6,4
NRS 06-15 W4	6	15,0	6,4
NRS 07-15 W4	7	15,0	6,4
NRS 08-15 W4	8	15,0	6,4
NRS 09-15 W4	9	15,0	6,4
NRS 10-15 W4	10	15,0	6,4
NRS 11-15 W4	11	15,0	6,4
NRS 12-15 W4	12	15,0	6,4
NRS 13-15 W4	13	15,0	6,4
NRS 14-15 W4	14	15,0	6,4
NRS 15-15 W4	15	15,0	6,4
NRS 16-15 W4	16	15,0	6,4
NRS 17-15 W4	17	15,0	6,4
NRS 18-15 W4	18	15,0	6,4
NRS 19-15 W4	19	15,0	6,4
NRS 20-15 W4	20	15,0	6,4
NRS 21-15 W4	21	15,0	6,4
NRS 22-15 W4	22	15,0	6,4
NRS 23-15 W4	23	15,0	6,4
NRS 24-15 W4	24	15,0	6,4
NRS 25-15 W4	25	15,0	6,4
NRS 26-15 W4	26	15,0	6,4
NRS 27-15 W4	27	15,0	6,4
NRS 28-15 W4	28	15,0	6,4
NRS 29-15 W4	29	15,0	6,4
NRS 30-15 W4	30	15,0	6,4
NRS 31-15 W4	31	15,0	6,4
NRS 32-15 W4	32	15,0	6,4
NRS 33-15 W4	33	15,0	6,4
NRS 34-15 W4	34	15,0	6,4
NRS 35-15 W4	35	15,0	6,4
NRS 36-15 W4	36	15,0	6,4
NRS 37-15 W4	37	15,0	6,4
NRS 38-15 W4	38	15,0	6,4
NRS 39-15 W4	39	15,0	6,4
NRS 40-15 W4	40	15,0	6,4

Varijante proizvoda

NRS (15 mm) Obujmica držača, Čelik

NRS (9 mm) Obujmica držača, Čelik

NRS (12 mm) Obujmica držača, Čelik

NRS W4 (12 mm) Obujmica držača, Krom-nikal čelik (1.4301)

NRS (20 mm) Obujmica držača, Čelik

NRS W4 (20 mm) Obujmica držača, Krom-nikal čelik (1.4301)

NRS (25 mm) Obujmica držača, Čelik