

## Karakteristike

|  |   |
|--|---|
| <b>Priključak</b>  | Priključci za ulje straga: A + B = G<br>3/8"; Ulje curenja = G 1/4"   |
| <b>Izvedba</b>   | Standardna varijanta<br>Type "C" with standard seal<br>Vratilo Ø 16mm |
| <b>Ulazni i povratni tlak s vodom za curenje ulja max.</b> | 140 bar   |



## Napomena

Preporučuje se opće priključivanje voda za curenje ulja!

## Artikli

| Naziv                | Protok max. (L/min) | Volumen trošenja (cc) | Broj okretaja min. (rpm) | Broj okretaja max. (rpm) | Okretni moment max. (N-m) | Pad tlaka max. (bar) | Pmax. at 0-100 rpm (bar) | Pmax. at 100-300 rpm (bar) | Pmax. at 300-600 rpm (bar) | Pmax. at 600 rpm (bar) | L (mm) | Težina (kg) |
|----------------------|---------------------|-----------------------|--------------------------|--------------------------|---------------------------|----------------------|--------------------------|----------------------------|----------------------------|------------------------|--------|-------------|
| <b>HK EPMM 008 C</b> | 16                  | 8,2                   | 50                       | 1950                     | 11                        | 100                  | 140                      | 100                        | 40                         | 20                     | 104    | 1,9         |
| <b>HK EPMM 012 C</b> | 20                  | 12,9                  | 40                       | 1550                     | 16                        | 100                  | 140                      | 100                        | 40                         | 20                     | 106    | 2,0         |
| <b>HK EPMM 020 C</b> | 20                  | 20,0                  | 30                       | 1000                     | 25                        | 100                  | 140                      | 100                        | 40                         | 20                     | 109    | 2,1         |
| <b>HK EPMM 032 C</b> | 20                  | 31,8                  | 30                       | 630                      | 40                        | 100                  | 140                      | 100                        | 40                         | -                      | 114    | 2,2         |
| <b>HK EPMM 040 C</b> | 20                  | 40,0                  | 25                       | 500                      | 41                        | 80                   | 140                      | 100                        | 40                         | -                      | 118    | 2,3         |
| <b>HK EPMM 050 C</b> | 20                  | 50,0                  | 20                       | 400                      | 45                        | 70                   | 140                      | 100                        | -                          | -                      | 122    | 2,4         |

max. pressure on shaft seal (without leak oil line) or pressure in leak oil line – Vrijednosti za okretni moment i padove tlaka vrijede za trajni pogon

## Pribor

**HK EPMM F** Prirubnica za Gerotor motor

## Rezervni dijelovi

**HK EP DS** Brtveni set za hidraulični planetarni motor