

## Karakteristike

<b>Priključak</b>	Priključci za ulje: A + B = G 1/2"; Ulje curenja = G 1/4"
<b>Izvedba</b>	Standardna varijanta Type "C" with standard seal Four hole flange bolt circle 106,4 Vratilo Ø 32mm
<b>Ulazni i povratni tlak s vodom za curenje ulja max.</b>	210 bar



## Napomena

Preporučuje se opće priključivanje voda za curenje ulja!

## Artikli

Naziv	Protok max. (L/min)	Volumen trošenja (cc)	Broj okretaja min. (rpm)	Broj okretaja max. (rpm)	Okretni moment max. (N-m)	Pad tlaka max. (bar)	Pmax. at 0-100 rpm (bar)	Pmax. at 100-300 rpm (bar)	Pmax. at 300 rpm (bar)	L (mm)	Težina (kg)
HK EPMS 080 C	65	80,5	10	810	200	175	100	50	20	166	9,8
HK EPMS 100 C	75	100,0	10	750	290	175	100	50	20	169	10,0
HK EPMS 125 C	75	125,7	8	600	370	175	100	50	20	174	10,3
HK EPMS 160 C	75	159,7	8	470	460	150	100	50	20	180	10,7
HK EPMS 200 C	75	200,0	8	375	460	140	100	50	20	187	11,1
HK EPMS 250 C	75	250,0	8	300	500	125	100	50	-	195	11,6
HK EPMS 315 C	75	314,9	8	240	540	120	100	50	-	207	12,3
HK EPMS 400 C	75	397,0	8	185	580	100	100	50	-	221	13,2

max. pressure on shaft seal (without leak oil line) or pressure in leak oil line – Vrijednosti za okretni moment i padove tlaka vrijede za trajni pogon – pmax = maks. tlak

## Pribor

HK V0 590 Šok ventil

## Rezervni dijelovi

HK EP DS Brtveni set za hidraulični planetarni motor