

DPS FPM

Set brtvi za jednodijelne klipove DPS-FPM


HANSA FLEX

Karakteristike

| | |
|-----------|---|
| Mediji | Mineralna ulja Emulzije vode |
| Materijal | (1) Brtva: FPM (2) Prsten za vođenje: acetal smola |
| Primjena | Hidraulika |



| Toleranz / Tolerance | | | | | | |
|----------------------|------------|------------|------------|--------|--------|--|
| D | d | L | G | M | P | |
| H11 | +0,10 0 | +0,25 0 | +0,10 0 | ± 0,05 | ± 0,15 | |



Artikli

| Naziv | D (mm) | d (mm) | L (mm) | G (mm) | M (mm) | P (mm) |
|-----------------|-----------|-----------|-----------|-----------|-----------|-----------|
| DPS 32 24-1 FPM | 32 | 24 | 10,0 | 4,00 | 29,0 | 31,0 |
| DPS 32 24 FPM | 32 | 24 | 10,0 | 4,00 | 29,0 | 31,0 |
| DPS 50 38 FPM | 50 | 38 | 20,5 | 4,20 | 46,0 | 49,4 |
| DPS 50 40-1 FPM | 50 | 40 | 12,5 | 4,00 | 47,0 | 49,0 |
| DPS 60 48 FPM | 60 | 48 | 20,5 | 4,20 | 56,0 | 59,4 |
| DPS 63 51 FPM | 63 | 51 | 20,5 | 4,20 | 59,0 | 62,4 |
| DPS 80 66 FPM | 80 | 66 | 22,5 | 5,20 | 76,0 | 79,4 |
| DPS 100 86 FPM | 100 | 86 | 22,5 | 5,20 | 96,0 | 99,4 |
| DPS 125 108 FPM | 125 | 108 | 26,5 | 7,20 | 121,0 | 124,4 |
| DPS 140 123 FPM | 140 | 123 | 26,5 | 7,20 | 136,0 | 139,4 |