


DPS FPM

Set brtvi za jednodijelne klipove DPS-FPM


HANSA FLEX

Karakteristike

Mediji	Mineralna ulja Emulzije vode
Materijal	(1) Brtva: FPM (2) Prsten za vođenje: acetal smola
Primjena	Hidraulika



Toleranz / Tolerance						
D	d	L	G	M	P	
H11	+0,10 0	+0,25 0	+0,10 0	± 0,05	± 0,15	



Artikli

Naziv	D (mm)	d (mm)	L (mm)	G (mm)	M (mm)	P (mm)
DPS 32 24-1 FPM	32	24	10,0	4,00	29,0	31,0
DPS 32 24 FPM	32	24	10,0	4,00	29,0	31,0
DPS 50 38 FPM	50	38	20,5	4,20	46,0	49,4
DPS 50 40-1 FPM	50	40	12,5	4,00	47,0	49,0
DPS 60 48 FPM	60	48	20,5	4,20	56,0	59,4
DPS 63 51 FPM	63	51	20,5	4,20	59,0	62,4
DPS 80 66 FPM	80	66	22,5	5,20	76,0	79,4
DPS 100 86 FPM	100	86	22,5	5,20	96,0	99,4
DPS 125 108 FPM	125	108	26,5	7,20	121,0	124,4
DPS 140 123 FPM	140	123	26,5	7,20	136,0	139,4