

## Karakteristike

<b>Područje primjene</b>	Agrarna tehnika Građevinska industrija Rudarstvo Brodogradnja
<b>Posebna obilježja</b>	najveća čvrstoća na vlak i kidanje nema rastezanja pod tlakom ravno namatanje i bez međuspajanja
<b>Unutrašnji sloj</b>	PVC
<b>Umetak</b>	pleteni umetak od poliestera
<b>Vanjski sloj</b>	PVC
<b>Boja</b>	plava
<b>Temperatura min.</b>	-10 °C
<b>Temperatura max.</b>	60 °C
<b>Mediji</b>	Voda



## Artikli

Naziv	Col	Unutarnji Ø (mm)	BD* kod 20°C (bar)	Tlak pucanja (bar)	Duljina valjaka (m)
EURO WAS 1 BL	1"	25	8,5	25,5	100
EURO WAS 1 1/4 BL	1.1/4"	32	8,5	25,5	100
EURO WAS 1 1/2 BL	1.1/2"	38	8,5	25,5	100
EURO WAS 2 BL	2"	51	6,5	19,5	100
EURO WAS 2 1/2 BL	2.1/2"	63	6,5	19,5	100
EURO WAS 3 BL	3"	76	5,5	16,5	100
EURO WAS 4 BL	4"	102	5,5	16,5	100
EURO WAS 5 BL	5"	127	3,0	9,0	100
EURO WAS 6 BL	6"	152	3,0	9,0	100
EURO WAS 8 BL	8"	204	2,5	7,0	100

BD = radni tlak