

XV RD HB OS

Nazuvica sita

HANSA FLEX

Karakteristike

Područje primjene u građevini, rudarstvu i gradnji tunela

Priključak 1 Okrugli vanjski navoj

Priključak 2 BSP vanjski navoj, cilindrični

Norma DIN 20037

Mediji komprimirani zrak, voda

Materijal Čelik



Opis

Odgovara vijčanim spojevima stožastih tuljaca

Artikli

Naziv	Izvedba	G1	G2	Duljina (mm)	Konus	SW (mm)	Radni tlak bari
XVRD 32 HB 20 OS	bez filtra	Rd 32 x 1/8"	G 3/4" -14	48	1:3	32	PN 25
XVRD 38 HB 25 OS	bez filtra	Rd 38 x 1/8"	G 1" -11	54	1:3	41	PN 25
XVRD 46 HB 25 OS	bez filtra	Rd 46 x 1/6"	G 1" -11	58	1:3	46	PN 25
XVRD 46 HB 32 OS	bez filtra	Rd 46 x 1/6"	G 1,1/4" - 11	58	1:3	46	PN 25
XVRD 46 HB 40 OS	bez filtra	Rd 46 x 1/6"	G 1,1/2" - 11	63	1:3	50	PN 25
XVRD 55 HB 32 OS	bez filtra	Rd 55 x 1/6"	G 1,1/4" - 11	63	1:3	55	PN 25
XVRD 55 HB 40 OS	bez filtra	Rd 55 x 1/6"	G 1,1/2" - 11	68	1:3	55	PN 25
XVRD 55 HB 50 OS	bez filtra	Rd 55 x 1/6"	G 2" -11	68	1:3	75	PN 25
XVRD 62 HB 40 OS	bez filtra	Rd 62 x 1/6"	G 1,1/2" - 11	75	1:3	65	PN 25
XVRD 62 HB 50 OS	bez filtra	Rd 62 x 1/6"	G 2" -11	75	1:3	75	PN 25
XVRD 75 HB 40 OS	bez filtra	Rd 75 x 1/6"	G 1,1/2" - 11	80	1:3	75	PN 25
XVRD 75 HB 50 OS	bez filtra	Rd 75 x 1/6"	G 2" -11	85	1:3	75	PN 25

G1, G2 = navoji priključka 1, odn. 2 – SW = širina ključa