

WAS STRAHL

Crijevo za vodu u graditeljstvu

HANSA FLEX

Karakteristike

Posebna obilježja	visokosavittljivo i robusno bez LABS-a, sredstva za rastavljanje i masti mali protočni otpor
Unutrašnji sloj	crni, glatki EPDM unutrašnji sloj bez pora
Umetak	sintetička vlakna
Vanjski sloj	EPDM neosjetljiv na ozon i UV zrake
Boja	crna
Temperatura min.	-40 °C
Temperatura max.	95 °C
Temperaturno područje	najviše temperature do 110°C
Mediji	Voda



Napomena

Radni tlak odnosi se na sobnu temperaturu

Artikli

Naziv	Col	Unutarnji Ø (mm)	Debljina stjenki (mm)	Radni tlak (bar)	Radius savijanja min. (mm)	Duljina valjaka (m)
WAS 10-3.5 STRAHL	3/8"	10	3,5	20,0	60	50
WAS 13-3 STRAHL	1/2"	13	3,0	20,0	80	40
WAS 16-3.5 STRAHL	5/8"	16	3,5	20,0	100	40
WAS 19-4 STRAHL	3/4"	19	4,0	20,0	120	40
WAS 25-4.5 STRAHL	1"	25	4,5	20,0	150	40
WAS 32-6 STRAHL	1.1/4"	32	6,0	20,0	200	50