

# WAS STRAHL

Crijevo za vodu u graditeljstvu

**HANSA FLEX**

## Karakteristike

<b>Posebna obilježja</b>	visokosavittljivo i robusno bez LABS-a, sredstva za rastavljanje i masti mali protočni otpor
<b>Unutrašnji sloj</b>	crni, glatki EPDM unutrašnji sloj bez pora
<b>Umetak</b>	sintetička vlakna
<b>Vanjski sloj</b>	EPDM neosjetljiv na ozon i UV zrake
<b>Boja</b>	crna
<b>Temperatura min.</b>	-40 °C
<b>Temperatura max.</b>	95 °C
<b>Temperaturno područje</b>	najviše temperature do 110°C
<b>Mediji</b>	Voda



## Napomena

Radni tlak odnosi se na sobnu temperaturu

## Artikli

Naziv	Col	Unutarnji Ø (mm)	Debljina stjenki (mm)	Radni tlak (bar)	Radius savijanja min. (mm)	Duljina valjaka (m)
<b>WAS 10-3.5 STRAHL</b>	3/8"	10	3,5	20,0	60	50
<b>WAS 13-3 STRAHL</b>	1/2"	13	3,0	20,0	80	40
<b>WAS 16-3.5 STRAHL</b>	5/8"	16	3,5	20,0	100	40
<b>WAS 19-4 STRAHL</b>	3/4"	19	4,0	20,0	120	40
<b>WAS 25-4.5 STRAHL</b>	1"	25	4,5	20,0	150	40
<b>WAS 32-6 STRAHL</b>	1.1/4"	32	6,0	20,0	200	50