

# MULTI EPDM

Univerzalno crijevo

**HANSA FLEX**

## Karakteristike

<b>Područje primjene</b>	Agrarna tehnika Građevinska industrija Građnja postrojenja
<b>Posebna obilježja</b>	otporno na ozon, ulja i vremenske utjecaje
<b>Unutrašnji sloj</b>	EPDM
<b>Umetak</b>	sintetička vlakna
<b>Vanjski sloj</b>	Kloropren guma
<b>Boja</b>	crna
<b>Temperatura min.</b>	-40 °C
<b>Temperatura max.</b>	120 °C



## Artikli

Naziv	Col	Unutarnji Ø (mm)	Vanjski Ø (mm)	Debljina stjenki (mm)	Radni tlak (bar)	Tlak pucanja (bar)	Radius savijanja min. (mm)
<b>MULTI 13-3.2 EPDM</b>	1/2"	13,0	19,4	3,2	30,0	90	130
<b>MULTI 19-4.2 EPDM</b>	3/4"	19,0	27,4	4,2	25,0	75	190
<b>MULTI 25-4.5 EPDM</b>	1"	25,0	34,0	4,5	20,0	60	250
<b>MULTI 32-5.5 EPDM</b>	1.1/4"	32,0	43,0	5,5	12,0	36	320
<b>MULTI 38-6 EPDM</b>	1.1/2"	38,0	50,0	6,0	12,0	36	380
<b>MULTI 51-8.5 EPDM</b>	2"	50,8	68,0	8,6	7,0	70	510