


MULTI EPDM

Univerzalno crijevo

HANSA FLEX

Karakteristike

| | |
|-------------------|--|
| Područje primjene | Agrarna tehnika Građevinska industrija Građnja postrojenja |
| Posebna obilježja | otporno na ozon, ulja i vremenske utjecaje |
| Unutrašnji sloj | EPDM |
| Umetak | sintetička vlakna |
| Vanjski sloj | Kloropren guma |
| Boja | crna |
| Temperatura min. | -40 °C |
| Temperatura max. | 120 °C |



Artikli

| Naziv | Col | Unutarnji Ø (mm) | Vanjski Ø (mm) | Debljina stjenki (mm) | Radni tlak (bar) | Tlak pucanja (bar) | Radius savijanja min. (mm) |
|-------------------|--------|---------------------|-------------------|--------------------------|---------------------|-----------------------|-------------------------------|
| MULTI 13-3.2 EPDM | 1/2" | 13,0 | 19,4 | 3,2 | 30,0 | 90 | 130 |
| MULTI 19-4.2 EPDM | 3/4" | 19,0 | 27,4 | 4,2 | 25,0 | 75 | 190 |
| MULTI 25-4.5 EPDM | 1" | 25,0 | 34,0 | 4,5 | 20,0 | 60 | 250 |
| MULTI 32-5.5 EPDM | 1.1/4" | 32,0 | 43,0 | 5,5 | 12,0 | 36 | 320 |
| MULTI 38-6 EPDM | 1.1/2" | 38,0 | 50,0 | 6,0 | 12,0 | 36 | 380 |
| MULTI 51-8.5 EPDM | 2" | 50,8 | 68,0 | 8,6 | 7,0 | 70 | 510 |